


PRODUCT DATA SHEET





An NSF registered H2, silicone lubricant for package handling applications. It eliminates the binding and sticking of packages and boxes, while protecting most

surfaces.

Applications

Recommended to lubricate package handling equipment

such as chutes, slides, guides and rails.

Unit Package Description

CRC

5 Gallon Pail

Generic Description 1 Silicone Lubricant

Net Fill 5 Gal

UPC Code 078254032221

Unit Dimensions 13.75H x 11.25W x 11.25D in

Units Per Case

Case Dimensions 13.8H x 11.3W x 11.3D in

Cases Per Pallet 24 Case Weight 33 lbs

Clear Light Yellow Liquid **Appearance** Base Type Poly dimthylsiloxane

113°F Flash point (F) 45°C Flash point (C)

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.75

Plastic Safe Safe on Most Plastics (Test small area)

Film Type Wet

Film Thickness Not Determined

Slow **Evaporation Rate**

Dielectric Strength Not Determined Working Temp (F) -40 to 400°F -40 to 204.4°C Working Temp (C)

Last revised: 12/28/2017

Page 1 of 2



of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified



PRODUCT DATA SHEET



Propellant None NSF Category Code H2

NSF Number 139430

DOT Proper Shipping Name Not Regulated

VOC % (Consumer Product 90.4

def)

VOC g/L (Consumer 684.8

Product def)

VOC lbs/gal (Consumer 5.7

Prod def)

VOC Category Not Regulated (Single Purpose Lubricant)

Removal (How To) Remove with Petroleum Distillates.

Last revised: 12/28/2017

Page 2 of 2

