

LED BR20, BR30, BR40



+25,000
hours*

120°
beam
spread

dimmable

80/90
CRI

features

- Direct replacement for incandescent BR/R lamps
- 80% more efficient and 30x longer life than standard incandescent
- Smooth aluminum body with ANSI standard form factor
- Comfortable diffused light
- Instant-on with no warm up, unlike CFLs
- +25,000 hour rated life for ENERGY STAR® Approved lamps*
- 50,000 hour design life**
- Choice of 2700K, 3000K, 4000K, or 5000K color temperatures
- Acceptable for ICAT rated downlights
- Shatter resistant for reduced risk of injury and breakage

RoHS
Compliant



cUL US LISTED

performance

- BR20 – 500 lumen replaces 50W incandescent
- BR30 – 685 lumen replaces 50W incandescent
- BR30 – 800 lumen replaces 65W incandescent
- BR40 – 685 lumen replaces 50W incandescent
- BR40 – 1000 lumen replaces 85W incandescent
- BR40 – 1200 lumen replaces 120W incandescent
- 120V @ 60Hz
- Dry and damp location rated
- Not for use in totally enclosed fixtures
- Not for use with electronic timers, photocells, or motion/occupancy sensors

applications

- Recessed Lighting
- Accent / Display Lighting
- Retail / Residential
- Hospitality
- Track Lighting
- Healthcare
- Office
- Hotel

* Early initial qualification for ENERGY STAR allows for directional lamp life claims of 25,000 hours (L70) with 3,000 hour actual test data, LM80 data and in-situ temperature measurements. As the lamps pass ENERGY STAR requirements, manufacturers may increase the lifetime of a product as dictated by ENERGY STAR guidelines. See http://www.energystar.gov/index.cfm?fuseaction=products_for_partners.showLightbulbs for further details.

** Design life is based on engineering testing and probability analysis



LED BR20, BR30, BR40

ordering information

	Order Code	Item #	W	Lm	CCT	CRI	Bm	MOL	Life/Hrs*	Replaces Incandescent	
BR20	08667	LED8WBR20/840K-DIM-G4	8W	550	4000K	80+	120°	3.74"	25,000	50W R20	
	08932	LED7WBR20/827K-DIM-G5	7W	550	2700K	80+	120°	3.82"	25,000	55W R20	★
	08933	LED7WBR20/830K-DIM-G5	7W	550	3000K	80+	120°	3.82"	25,000	55W R20	★
	08935	LED7WBR20/840K-DIM-G5	7W	550	4000K	80+	120°	3.82"	25,000	55W R20	★
BR30	08998	LED8WBR30/827K-DIM-G5	8W	650	2700K	80+	120°	5.08"	25,000	65W BR30	★
	08999	LED8WBR30/830K-DIM-G5	8W	650	3000K	80+	120°	5.08"	25,000	65W BR30	★
	09000	LED8WBR30/840K-DIM-G5	8W	650	4000K	80+	120°	5.08"	25,000	65W BR30	★
	08936	LED11WBR30/827K-DIM-G5	11W	850	2700K	80+	120°	5.08"	25,000	65W BR30	★
	08937	LED11WBR30/830K-DIM-G5	11W	850	3000K	80+	120°	5.08"	25,000	65W BR30	★
	08938	LED11WBR30/840K-DIM-G5	11W	850	4000K	80+	120°	5.08"	25,000	65W BR30	★
	09111	LED11WBR30/850K-DIM-G5	11W	850	5000K	80+	120°	5.08"	25,000	65W BR30	★
	09092	LED11WBR30/PINK-DIM-G5	11W	N/A	PINK	N/A	120°	5.08"	25,000	65W BR30	
	08945	LED12WBR30/927K-DIM-G5	12W	800	2700K	90+	120°	5.08"	25,000	65W BR30	★
	08946	LED12WBR30/930K-DIM-G5	12W	800	3000K	90+	120°	5.08"	25,000	65W BR30	★
BR40	90066	LED13WBR40/827K-DIM-G4	13W	1,000	2700K	80+	120°	6.30"	25,000	85W BR40	★
	90064	LED13WBR40/840K-DIM-G4	13W	1,000	4000K	80+	120°	6.30"	25,000	85W BR40	★
	90047	LED17WBR40/827K-DIM-G4	17W	1,400	2700K	80+	120°	6.30"	25,000	100W BR40	★
	90046	LED17WBR40/830K-DIM-G4	17W	1,400	3000K	80+	120°	6.30"	25,000	100W BR40	★
	90045	LED17WBR40/840K-DIM-G4	17W	1,400	4000K	80+	120°	6.30"	25,000	100W BR40	★
	08940	LED12WBR40/830K-DIM-G5	12W	1,050	3000K	80+	120°	6.26"	25,000	80W BR40	★
	08943	LED17WBR40/830K-DIM-G5	17W	1,400	3000K	80+	120°	6.26"	25,000	100W BR40	★
	08944	LED17WBR40/840K-DIM-G5	17W	1,400	4000K	80+	120°	6.26"	25,000	100W BR40	★

NOTE: use order code when ordering.

* 25,000 hour ENERGY STAR® rated life. 50,000 hour design life. See note on obverse.

★ENERGY STAR® Approved

watch > like > follow



23220 W. 84th St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975
 Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335