

LED T8 Direct Fit Replacement Lamps : Glass



2'/4'
length

8/
11.5/15
watts

157+
lpw

50K
hours

Features

- Directly replaces all 2ft and 4ft F32T8 (32W, 28W, 25W) lamps
- No socket changes, uses shunted or non-shunted sockets
- Operates on most electronic T8 (instant & programmed) and battery backup ballasts
- Instantaneous full light output upon power-up
- 11.5/15W available with shatterproof PET coating
- Choice of 3500K, 4000K, or 5000K CCT
- NSF listed for commercial foodservice equipment
- Frosted glass lens reduces visual glare
- Environment-friendly, no mercury or lead
- 5 year product warranty
- Suitable for use in totally enclosed fixtures
- No rewiring or modifications of any kind required



Performance

- 2': 1,200/1,250 lumens @ 8W
- 4': 1,700/1,800 lumens @ 11.5W
- 4': 2,100/2,200 lumens @ 15W
- 80+ CRI
- Beam Angle: 220°
- THD: <20%
- Power Factor: 0.98
- Rated Lifetime: 50,000 hours @ L70
- UL listed for damp locations
- Suitable for use in fixtures where ambient temperature is between -4°F (-20°C) and 113°F (45°C)
- Does not operate on magnetic ballasts
- Does not operate on T12 ballasts
- Can be operated on fluorescent battery backup
- **See eiko.com for a list of tested ballasts**

Applications

- Highbays
- Troffers
- Industrial Strips
- Cove Lighting
- Vapor Tights
- Warehouses
- Stairwells
- Cold Storage



selection. solutions. simplicity. eiko.com

LED T8 Direct Fit Replacement Lamps : Glass

Photometrics



Ordering Information

Order Code	Item #	Length	Lm	Nominal W	V (Ballast Dependent)	Emergency Ballast Compatible	CCT	CRI	Glass Tube	Bm	Life/Hrs	DLC
60440	LED8WT8/24/835-G7DR	2'	1,200	8W	120-277V, 347V	✓	3500K	80+	Frosted	220°	50K	✓
60441	LED8WT8/24/840-G7DR	2'	1,250	8W	120-277V, 347V	✓	4000K	80+	Frosted	220°	50K	✓
60442	LED8WT8/24/850-G7DR	2'	1,250	8W	120-277V, 347V	✓	5000K	80+	Frosted	220°	50K	✓
60443	LED11.5WT8/48/835-G7DR	4'	1,700	11.5W	120-277V, 347V	✓	3500K	80+	Frosted	220°	50K	✓
60444	LED11.5WT8/48/840-G7DR	4'	1,800	11.5W	120-277V, 347V	✓	4000K	80+	Frosted	220°	50K	✓
60445	LED11.5WT8/48/850-G7DR	4'	1,800	11.5W	120-277V, 347V	✓	5000K	80+	Frosted	220°	50K	✓
09559	LED15WT8/48/835-G7DR	4'	2,100	15W	120-277V, 347V	✓	3500K	80+	Frosted	220°	50K	✓
09560	LED15WT8/48/840-G7DR	4'	2,200	15W	120-277V, 347V	✓	4000K	80+	Frosted	220°	50K	✓
09561	LED15WT8/48/850-G7DR	4'	2,200	15W	120-277V, 347V	✓	5000K	80+	Frosted	220°	50K	✓
09562	LED11.5WT8/48/835-PET-G7DR	4'	1,700	11.5W	120-277V, 347V	✓	3500K	80+	Frosted	220°	50K	
09563	LED11.5WT8/48/840-PET-G7DR	4'	1,800	11.5W	120-277V, 347V	✓	4000K	80+	Frosted	220°	50K	
09564	LED11.5WT8/48/850-PET-G7DR	4'	1,800	11.5W	120-277V, 347V	✓	5000K	80+	Frosted	220°	50K	
09672	LED15WT8/48/835-PET-G7DR	4'	2,100	15W	120-277V, 347V	✓	3500K	80+	Frosted	220°	50K	
09673	LED15WT8/48/840-PET-G7DR	4'	2,200	15W	120-277V, 347V	✓	4000K	80+	Frosted	220°	50K	
09674	LED15WT8/48/850-PET-G7DR	4'	2,200	15W	120-277V, 347V	✓	5000K	80+	Frosted	220°	50K	

NOTE: Use order code when ordering.

✓ DesignLights Consortium® Qualified



NSF offers the most accepted and trusted certification and verification programs for commercial foodservice equipment, specified by health departments, restaurant buyers and specifiers worldwide. NSF means market access – products with the NSF mark receive guaranteed regulatory acceptance in North America and improved acceptance worldwide. Verification programs, such as HACCP Compliance Verification - EU, demonstrate hygienic quality, independently verified by a trusted source.

watch > like > follow



23220 W. 84th St, Shawnee, KS 66227 · (P) 1.800.852.2217 · (F) 1.800.492.8975
 Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 · (F) 1.888.705.1335