ELKAY®
SPECIFICATIONS

# Elkay Outdoor Fountain Wall Mount Non-Filtered Non-Refrigerated Freeze Resistant
# Model LK4405FRK

## PRODUCT SPECIFICATIONS

Elkay Outdoor Fountain Wall Mount Non-Filtered, Non-Refrigerated Freeze Resistant. Features shall include 316 Stainless, Heavy Duty Vandal-Resistant, Sealed Freeze Resistant. Furnished with Vandal-Resistant bubbler. Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On-Wall), for Outdoor applications, serving 1 station(s). Unit shall be lead-free design which is certified to NSF/ANSI 61 & 372 (lead free) and meets Federal and State low-lead requirements.

| | |
|---|---|
| **Special Features:** | 316 Stainless, Heavy Duty Vandal-Resistant, Sealed Freeze Resistant |
| **Finish:** | Beige (BGE), Black (BLK), Blue (BLU), Brown (BRN), Evergreen (EVG), Gray (GRY), Orange (ORN), Purple (PUR), Red (RED), Terracotta (TER), White (WHT), Yellow (YLW) |
| **Power:** | No Electrical Required |
| **Bubbler Style:** | Vandal-Resistant |
| **Activation by:** | Mechanical Front Bubbler Button |
| **Mounting Type:** | Wall Mount (On-Wall) |
| **Chilling Option:** | Non-Refrigerated |
| **Dimensions (L x W x H):** | 14" x 19-1/8" x 8" |
| **Approx. Shipping Weight:** | 63 lbs. |
| **Installation Location:** | Outdoor |
| **No. of Stations Served:** | 1 |

- Mechanically-Activated bubbler continues to supply water in event of service disruptions.
- Base material constructed from marine-grade 316 stainless steel provides the ultimate corrosion protection from even the most corrosive elements.
- Heavy Duty Vandal-Resistant:
  - Tamper resistant screws
  - Resists stains and corrosion
  - Heavy-gauge construction
- Vandal-resistant, bubblers are one-piece, chrome plated with integral hood guard design to prevent contamination from other users, airborne deposits and tampering.
- Sealed Freeze Resistant Valve System: Fully sealed freeze resistant system that minimizes chance of ground water contamination, and prevents drain water from mixing with fresh water. Designed for ground installation below the frost line.






AMERICAN PRIDE. A LIFETIME TRADITION.
Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.

MADE IN USA

**Included with Product:** Outdoor Fountain, Freeze Resistant Box

**▼ Ships in multiple boxes.**

## PRODUCT COMPLIANCE

ADA & ICC A117.1

Buy American Act

NSF/ANSI 61 & 372 (lead free)

Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF)

**Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.**

Warranty (PDF)

## OPTIONAL ACCESSORIES

| |
|---|
| LK4471LHB - Locking Hose Bib |
| 97890C - Accessory - Direct Bury Adaptor |

PART:_____QTY: _____

PROJECT:_____

CONTACT:_____

DATE:_____

NOTES:_____

APPROVAL:_____

*In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.*


© 2018

## MOUNTING INSTRUCTIONS and PLUMBING CONNECTIONS

Refer to diagrams for plumbing rough-in. This fountain is to be mounted on a smooth, flat finished wall surface with adequate support.
**Note:** Wall mounting structure must be capable of supporting 300lb. load minimum on fountain. To secure unit, use 3/8 minimum fasteners (not provided). Water service line and waste line are to be assmbled as required. Final check for leaks and correct functions of fountain should be made. (For details see the installation instructions.)

The Freeze_Resistant package must be mounted on an interior wall in a heated area (See details in installation instructions.)


**Installation requires trap to be installed in wall. A service supply stop must be installed at the fountain inlet line. Trap and service stop not included.**

**Caution - Fountain must be securely bolted to wall.**


**Note:** For wall support required locations see installation instructions provided with fountain.

**OPERATING PRESSURES:** Supply water 20 – 105 psi maximum


## TOP VIEW




## MOUNTING BOLT & ACCESS HOLE LOCATION




## FRONT & SIDE VIEWS




**LEGEND**
A = Mounting screw or bolt locations.
B = 7/8" Ø (22mm) hole for water supply tube.
C = 7/8" Ø (22mm) hole for operating cable.
D = 2" Ø (51mm) holes for waste line.

*In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.*