




Materials/Finishes:	Electro-Galvanized with EPDM Insulation Liner (40HS)
Variants:	N/A
Service:	Designed for the suspension of insulated and non-insulated pipe lines.
Approvals:	Complies with Federal Specification WWH-171-E (Type# 25), A-A-1192A (Type# 12), Manufacturers' Standardization Society SP-58 and MSS SP-69 (Type# 12).
Ordering:	Specify figure number and CT or IPS Size.
Notes:	The "Handy Split" hinge device allows single handed installation. UV resistant EPDM ubber provides noise reduction. Temperature range is from -50° F through 230° F.

PIPE SIZE (IPS)	PIPE SIZE (CTS)	SCREW	A	B	C	D	WGT EACH (LBS)	MAX REC LOAD (LBS)
1/4	3/8	M6	3/8-16	7/8	2-3/16	1-3/8	.11	180
3/8	1/2	M6	3/8-16	15/16	2-3/8	1-1/2	.12	180
-	5/8	M6	3/8-16	1	2-3/8	1-5/8	.12	180
1/2	3/4	M6	3/8-16	1-1/16	2-9/16	1-3/4	.14	180
3/4	1	M6	3/8-16	1-3/16	2-3/4	2	.15	180
1	1-1/4	M6	3/8-16	1-1/4	3-1/8	2-1/4	.17	180
1-1/4	1-1/2	M6	3/8-16	1-7/16	3-1/2	2-1/2	.19	180
1-1/2	-	M6	3/8-16	1-9/16	3-3/4	2-3/4	.20	180
-	2	M6	3/8-16	1-11/16	3-15/16	3	.26	180
2	-	M6	3/8-16	1-3/4	4-1/8	3-1/4	.27	180
-	2-1/2	M6	3/8-16	1-15/16	4-7/16	3-1/2	.29	300
2-1/2	-	M6	3/8-16	2-1/16	4-3/4	3-3/4	.36	300
-	3	M6	3/8-16	2-1/4	5	4-1/16	.38	300
3	-	M6	3/8-16	2-7/16	5-7/16	4-7/16	.41	300
-	3-1/2	M6	3/8-16	2-1/2	5-9/16	4-9/16	.41	300
3-1/2	4	M6	3/8-16	2-3/4	6-1/8	5-1/16	.67	300
4	-	M6	3/8-16	2-15/16	6-7/16	5-7/16	.70	300

PROJECT INFORMATION			APPROVAL STAMP	
Project:			Notes:	
Address:				
Contractor:				
Engineer:				
Date:				
Approved	Approved as Noted	Not Approved		