# Safety Data Sheet



Revision Number: 003.1

**1. PRODUCT AND COMPANY IDENTIFICATION** 

Product name:

**INHIBITOR known as P3 PREVOX 6767** 

Product type: Restriction of Use: Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

**BONDERITE S-FN 6767 CORROSION** Lubricant None identified

**IDH number:** 

595793

Region: United States **Contact information:** Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW WARNING: CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS       | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION    | 2               |
| EYE IRRITATION     | 2A              |
| SKIN SENSITIZATION | 1               |



### **Precautionary Statements**

| Prevention: | Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling.<br>Contaminated work clothing should not be allowed out of the workplace. Wear protective  |
|-------------|--|
|             | gloves, eye protection, and face protection.   |
| Response:   | IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. |
| Storage:    | Not prescribed   |
| Disposal:   | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.  |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

### See Section 11 for additional toxicological information.

#### 3. **COMPOSITION / INFORMATION ON INGREDIENTS**

| Hazardous Component(s)                                 | CAS Number  | Percentage* |
|--|-------------|-------------|
| Distillates (petroleum), hydrotreated light naphthenic | 64742-53-6  | 60 - 100    |
| Amine soap   | Proprietary | 10 - 30     |
| Barium sulfonate                                       | 61790-48-5  | 1 - 5       |
| Barium compound  | 513-77-9    | 1 - 5       |
| Diethanolamine   | 111-42-2    | 0.1 - 1     |

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

| Inhalation:         | If mist or vapor of this product is inhaled, remove person immediately to free   |
|---------------------|--|
|                     | air. Seek medical attention if symptoms develop or persist.  |
| Skin contact:       | Remove contaminated clothing and footwear. Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medic attention. |
| Eye contact:        | Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.                                 |
| Ingestion:          | Get immediate medical attention. Do not induce vomiting.   |
| Symptoms:           | See Section 11.  |
| Notes to physician: | This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.                                   |

| Extinguishing media:               | Water spray (fog), foam, dry chemical or carbon dioxide. In case of fire, keep containers cool with water spray. |
|------------------------------------|--|
| Special firefighting procedures:   | Wear full protective clothing. Wear self-contained breathing apparatus.  |
| Unusual fire or explosion hazards: | This product is combustible at high temperatures.  |
| Hazardous combustion products:     | Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. |

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| Environmental precautions: | Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up.   |
|----------------------------|---|
| Clean-up methods:          | Absorb spill with inert material. Shovel material into appropriate container for<br>disposal. Ventilate area. Dispose of according to Federal, State and local<br>governmental regulations. |

# 7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Do not take internally. For industrial use only. Use only with adequate ventilation. Launder work clothes frequently.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Manufacturer recommends storing above 4.4 °C (40 °F). If stored outside of this range, mix well before using. Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty containers.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                                    | ACGIH TLV   | OSHA PEL   | AIHA WEEL | OTHER |
|---|---|--|-----------|-------|
| Distillates (petroleum), hydrotreated light<br>naphthenic | Included in the<br>regulation but with no<br>data values. See<br>regulation for further<br>details<br>Exposure by all<br>routes should be<br>carefully controlled to<br>levels as low as<br>possible. | 5 mg/m3 TWA mist<br>10 mg/m3 TWA mist<br>500 ppm (2,000<br>mg/m3) PEL<br>5 mg/m3 PEL Mist. | None      | None  |
| Amine soap  | None  | None   | None      | None  |
| Barium sulfonate 0.5 mg/m3 TW<br>Ba)                      |   | 0.5 mg/m3 PEL (as<br>Ba)   | None      | None  |
| Barium compound   | 0.5 mg/m3 TWA (as<br>Ba)  | 0.5 mg/m3 PEL (as<br>Ba)   | None      | None  |
| Diethanolamine  | 1 mg/m3 TWA<br>Inhalable fraction and<br>vapor.<br>(SKIN) Inhalable<br>fraction and vapor.  | None   | None      | None  |

Engineering controls:

Respiratory protection:

Eye/face protection:

Skin protection:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that follows 29 CFR 1910.134 must be followed. If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Wear chemical goggles; face shield (if splashing is possible).

Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Liquid amber Mineral oil Not available. 9.0 - 9.5

Product name: BONDERITE S-FN 6767 CORROSION INHIBITOR known as P3 PREVOX 6767 Page 3 of 6

| Vapor pressure:                          |
|--|
| Boiling point/range:                     |
| Melting point/ range:                    |
| Specific gravity:                        |
| Vapor density:                           |
| Flash point:                             |
| Flammable/Explosive limits - lower:      |
| Flammable/Explosive limits - upper:      |
| Autoignition temperature:                |
| Flammability:                            |
| Evaporation rate:                        |
| Solubility in water:                     |
| Partition coefficient (n-octanol/water): |
| VOC content:                             |
| Viscosity:                               |
| Decomposition temperature:               |

Not determined > 400 °F (> 204.4 °C) Not available. 0.91 - 0.94 at 15.6 °C (60.08 °F) Not determined > 280 °F (> 137.78 °C) Not applicable Not applicable Not applicable Not applicable Not available. Appreciable Not available. Not determined Not available. Not available.

# 10. STABILITY AND REACTIVITYStability:Stable at normal conditions.Hazardous reactions:None under normal processing.Hazardous decomposition<br/>products:Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low<br/>molecular weight hydrocarbons. Oxides of nitrogen.Incompatible materials:Strong oxidizing agents. Strong acids.Reactivity:Nitrites may react with organic amines to form nitrosamines which can cause cancer.Conditions to avoid:Avoid excessive heat and ignition sources.

### **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure:

Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

| Inhalation:   | Inhalation of vapors or mists of the product may be irritating to the respiratory system.   |
|---------------|---|
| Skin contact: | Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.<br>This product is irritating to the skin. This product may cause an allergic skin reaction. A |
|               | component in this product may be absorbed through the skin in harmful amounts.  |
| Eye contact:  | Contact with this product may cause severe eye damage.  |
| Ingestion:    | Ingestion of this product may cause nausea, vomiting and diarrhea. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.                   |

| Hazardous Component(s)                                 | LD50s and LC50s   | Immediate and Delayed Health Effects   |  |
|--|---|--|--|
| Distillates (petroleum), hydrotreated light naphthenic | None  | Irritant   |  |
| Amine soap   | None  | Irritant, Allergen, Corrosive, Skin, Liver,<br>Kidney, Nervous System, Lung, Heart,<br>Reproductive, Thyroid, Pancreas, Blood,<br>Adrenals |  |
| Barium sulfonate                                       | None  | No Records   |  |
| Barium compound  | Oral LD50 (Rat) = 418 mg/kg<br>Oral LD50 (Mouse) = 200 mg/kg<br>Oral LD50 (Rat) = 630 - 750 mg/kg | Reproductive, Gastrointestinal, Kidney,<br>Nervous System, Cardiac, Lung, Blood,<br>Metabolic  |  |
| Diethanolamine   | Oral LD50 (Rat) = 710 mg/kg<br>Oral LD50 (Rat) = 1.82 g/kg  | Allergen, Corrosive, Irritant, Liver, Respiratory  |  |

| Hazardous Component(s)                                 | NTP Carcinogen                   | IARC Carcinogen | OSHA Carcinogen<br>(Specifically Regulated) |
|--|----------------------------------|-----------------|---|
| Distillates (petroleum), hydrotreated light naphthenic | Known To Be Human<br>Carcinogen. | Group 1         | No  |
| Amine soap   | No                               | No              | No  |
| Barium sulfonate                                       | No                               | No              | No  |
| Barium compound  | No                               | No              | No  |
| Diethanolamine   | No                               | Group 2B        | No  |

### **12. ECOLOGICAL INFORMATION**

**Ecological information:** 

Not available.

# **13. DISPOSAL CONSIDERATIONS**

### Information provided is for unused product only.

Recommended method of disposal:

Hazardous waste number:

Dispose of according to Federal, State and local governmental regulations.

Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA.

### **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

RQ, Environmentally hazardous substance, liquid, n.o.s. 9

Proper shipping name: Hazard class or division: Identification number: Packing group: DOT Hazardous Substance(s):

UN 3082 III Diethanolamine

| International Air Transportation (ICAO/IATA |   |
|---|---|
| Proper shipping name:                       | RQ, Environmentally hazardous substance, liquid, n.o.s. |
| Hazard class or division:                   | 9   |
| Identification number:                      | UN 3082   |
| Packing group:                              | III   |
| Water Transportation (IMO/IMDG)             |   |
| Proper shipping name:                       | RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. |
| Hazard class or division:                   | 9   |
| Identification number:                      | UN 3082   |
| Packing group:                              | III   |
|   |   |

# **15. REGULATORY INFORMATION**

**United States Regulatory Information** 

| CEPA DSL/NDSL Status:  | All components are listed on or are exempt from listing on the Canadian Domestic Substances List.   |
|--|---|
| Canada Regulatory Information  |   |
| California Proposition 65:   | No California Proposition 65 listed chemicals are known to be present.  |
| CERCLA Reportable quantity:  | CFR 372). Barium sulfonate (CAS# 61790-48-5). Barium compound (CAS# 513-77-9).<br>Diethanolamine (CAS# 111-42-2) 100 lbs. (45.4 kg)   |
| CERCLA/SARA Section 302 EHS:<br>CERCLA/SARA Section 311/312:<br>CERCLA/SARA Section 313: | None above reporting de minimis.<br>Immediate Health, Delayed Health<br>This product contains the following toxic chemicals subject to the reporting requirements of<br>section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 |
| TSCA 12 (b) Export Notification:   | None above reporting de minimis   |
| TSCA 8 (b) Inventory Status:   | All components are listed or are exempt from listing on the Toxic Substances Control Act<br>Inventory.  |

### **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: Corrected information in Section(s): 2

Prepared by: Jennifer Mckay, Regulatory Affairs Specialist

**Issue date:** 04/05/2016

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.