

Revision Number: 001.3 Issue date: 06/07/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE L-FG F 31 GRAPHITE IDH number:

FORGING LUBRICANT ACHESON known as DELTAFORGE F-31

Product type: Lubricant

Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 1224662

Region: United States

Contact information: Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)
None

Precautionary Statements

IDH number: 1224662

Prevention: Not prescribed Response: Not prescribed Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Graphite	7782-42-5	10 - 30

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Immediately wash skin thoroughly with soap and water. If symptoms develop

and persist, get medical attention.

Eye contact: Immediately flush eyes with water for at least 15 minutes, while holding

eyelids open. Seek medical attention at once.

Ingestion: Get immediate medical attention. Do not induce vomiting.

Symptoms: See Section 11.

IDH number: 1224662

Notes to physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: Not a fire hazard. This product is an aqueous mixture which will not burn.

Hazardous combustion products: Thermal decomposition can lead to release of irritating gases and vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of

this product. Use only with adequate ventilation.

Storage: For safe storage, store between 5.0 °C (41°F) and 30.0 °C (86°F)

Keep container closed. Store in a cool, dry, well-ventilated area. Storage within given temperature limit Outside temperature limits, the properties of the product will change. Protect from direct sunlight. Keep from freezing. Protect

from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection: Suitable protective clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Black Odor: Ammonia Odor threshold: Not available. pH: 11.0 - 11.5 Vapor pressure: Not determined Boiling point/range: > 100 °C (> 212°F) Melting point/ range: <= 0 °C (<= 32°F) Specific gravity: 1.05 - 1.15 Vapor density: Not available. Flash point: Not applicable Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not applicable Flammability Not applicable **Evaporation rate:** Not available.

Solubility in water: Disperses in water as a suspension

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not determined

Not applicable

700 - 1,000 mPa.s

Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

Incompatible materials: This product may react with strong acids or oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Avoid excessive heat and ignition sources. Freezing conditions.

IDH number: 1224662 Product name: BONDERITE L-FG F 31 GRAPHITE FORGING LUBRICANT ACHESON known as DELTAFORGE F-31

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation.

Skin contact: May cause skin irritation.

Eye contact: May cause irritation. This product may be severely irritating to the eyes. **Ingestion:** Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Graphite	None	Lung	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Graphite	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

IDH number: 1224662 Product name: BONDERITE L-FG F 31 GRAPHITE FORGING LUBRICANT ACHESON known as DELTAFORGE F-31

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

IDH number: 1224662

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2,3,9,11

Prepared by: Jennifer Mckay, Regulatory Affairs Specialist

Issue date: 06/07/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: BONDERITE L-FG F 31 GRAPHITE FORGING LUBRICANT ACHESON known as DELTAFORGE F-31