



Revision Number: 002.0

Issue date: 01/23/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE AA H4800 490ML PT A	IDH number:	2061871
Product type:	Structural adhesive	Item number:	2061246_2055240
Restriction of Use:	None identified	Region:	Canada
Company address:	Contact information:		
Henkel Canada Corporation	Telephone: +1 (905) 814-6511		
Meadowpine Boulevard 2515	MEDICAL EMERGENCY Phone: Poison Control Center		
Mississauga, Ontario L5N 6C3	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOR.
CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE RESPIRATORY IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention:	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
Response:	If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Storage:	
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local

IDH number: 2061871

Product name: LOCTITE AA H4800 490ML PT A

governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Methyl methacrylate	80-62-6	50 - 60
2-Hydroxyethyl methacrylate	868-77-9	10 - 20
Methacrylic acid	79-41-4	1 - 5
Butyl hydroxytoluene	128-37-0	1 - 5
Tert-butyl perbenzoate	614-45-9	0.1 - 1
Talc	14807-96-6	0.1 - 1
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Oxides of sulfur. Hydrogen chloride. Hydrogen sulfide. Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
-----------------------------------	---

Clean-up methods:

Remove all sources of ignition. Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material. Keep container closed.

Storage:

For safe storage, store between 2 °C (35.6 °F) and 8 °C (46.4 °F) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Protect from direct sunlight. Maintain head space in storage containers to support oxygen requirements of the inhibitor(s).

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methyl methacrylate	50 ppm TWA 100 ppm STEL (Dermal sensitization)	100 ppm (410 mg/m3) PEL	None	50 ppm
2-Hydroxyethyl methacrylate	None	None	None	3 ppm Ceiling
Methacrylic acid	20 ppm TWA	None	None	None
Butyl hydroxytoluene	2 mg/m3 TWA Inhalable fraction and vapor.	None	None	None
Tert-butyl perbenzoate	None	None	None	None
Talc	2 mg/m3 TWA Respirable fraction.	0.1 mg/m3 TWA Respirable. 2.4 MPPCF TWA Respirable. 20 MPPCF TWA	None	50 ppm
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Paste, Liquid

Color:

Off white

Odor:

Acrylic

Odor threshold:

Not available.

pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	1.02
Vapor density:	Not available.
Flash point:	14 °C (57.2 °F) Setaflash Closed Cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	2.6 % Method 40 CFR Part 63 Appendix A to Subpart PPPP
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	May occur with excessive aging, excessive heat, polymerization catalyst, inhibitor depletion, direct sunlight and under oxygen-free atmospheres.
Hazardous decomposition products:	Oxides of carbon. Oxides of sulfur. Hydrogen chloride. Hydrogen sulfide. Toxic fumes. Irritating vapors.
Incompatible materials:	Bases. Acids. Oxidizing agents. Amines. Free radical initiators. Heavy metals. Peroxides. Reaction with reducing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight. Loss of polymerization inhibitor. Loss of dissolved air. Do not mix in batches greater than 100 grams (0.22 pounds) unless you plan to use immediately.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes
-------------------------------------	------------------------

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. Drowsiness. Dizziness.
Skin contact: Causes skin irritation. May cause allergic skin reaction.
Eye contact: Causes serious eye irritation.
Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Methyl methacrylate	Oral LD50 (Rat) = 7,800 mg/kg Oral LD50 (Rabbit) = 6,000 mg/kg Oral LD50 (Rat) = 9,400 mg/kg	Allergen, Irritant, Kidney, Liver, Mutagen, Nervous System, Respiratory
2-Hydroxyethyl methacrylate	Oral LD50 (Mouse) = 3,275 mg/kg Oral LD50 (Rat) = 11.2 g/kg Oral LD50 (Rat) = 5,050 mg/kg	Irritant, Allergen
Methacrylic acid	Oral LD50 (Mouse) = 1,332 mg/kg Oral LD50 (Mouse) = 1,600 mg/kg Oral LD50 (Mouse) = 1,250 mg/kg Oral LD50 (Rabbit) = 1,200 mg/kg Oral LD50 (Rat) = 1,060 mg/kg Oral LD50 (Rat) = 2,224 mg/kg Dermal LD50 (Rabbit) = 500 mg/kg Inhalation LC50 (Rat, 4 h) = 7.1 mg/l	Corrosive, Irritant, Allergen
Butyl hydroxytoluene	Oral LD50 (Mouse) = 1,040 mg/kg Oral LD50 (Rat) = 890 mg/kg	Irritant, Mutagen
Tert-butyl perbenzoate	None	Central nervous system, Irritant, Mutagen
Talc	None	Irritant, Lung, Some evidence of carcinogenicity
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methyl methacrylate	No	No	No
2-Hydroxyethyl methacrylate	No	No	No
Methacrylic acid	No	No	No
Butyl hydroxytoluene	No	No	No
Tert-butyl perbenzoate	No	No	No
Talc	No	Group 2B	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground
Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

15. REGULATORY INFORMATION**Canada Regulatory Information**

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 01/23/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.