

Revision Number: 003.0 Issue date: 10/12/2017

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:LOCTITE 577 TTL 250ML USIDH number:2068748Product type:Anaerobic SealantItem number:2068748Restriction of Use:None identifiedRegion:Canada

Company address:
Henkel Canada Corporation

Meadow pine Boulevard 2515 Mississauga, Ontario L5N 6C3 Contact information: Telephone: +1 (905) 814-6511

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: w ww.henkelna.com

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION. SUSPECTED OF CAUSING CANCER.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	2





#### **Precautionary Statements**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated w ork clothing should not be allow ed out of the w orkplace. Wear

protective gloves, clothing, eye and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye

irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store locked up.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

IDH number: 2068748 Product name: LOCTITE 577 TTL 250ML US

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*	
Tetramethylene dimethacrylate	2082-81-7	10 - 20	
Oleic acid 5.5EO	9004-96-0	10 - 20	
Methacrylic acid, monoester w ith 1,2- propanediol, polymer w ith 4,4'- methylenediphenyl diisocyanate	190208-19-6	10 - 20	
Polyglycol dimethacrylate	109-16-0	5 - 10	
Ethene, homopolymer	9002-88-4	1 - 5	
Ethene, tetrafluoro-, homopolymer	9002-84-0	1 - 5	
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5	•
Propane-1,2-diol	57-55-6	1 - 5	
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1	
Cumene hydroperoxide	80-15-9	0.1 - 1	
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	123-26-2	0.1 - 1	

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

**Skin contact:** Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. Get medical

attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Irritating organic vapours. Acids. Ketones. Aldehydes.

Alcohols. Fluorine. Toxic fluorine compounds.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sew er or waterways.

Clean-up methods:

Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; we arfull protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, saw dust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

# 7. HANDLING AND STORAGE

**Handling:** Use only w ith adequate ventilation. Prevent contact w ith eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

Storage: For safe storage, store between 8 °C (46.4 °F) and 21 °C (69.8 °F)

Shelf Life Statement: Not available.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Tetramethylene dimethacrylate	None	None	None	None
Oleic acid 5.5EO	None	None	None	None
Methacrylic acid, monoester w ith 1,2-propanediol, polymer w ith 4,4'-methylenediphenyl diisocyanate	None	None	None	None
Polyglycol dimethacrylate	None	None	None	None
Ethene, homopolymer	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles.	15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Ethene, tetrafluoro-, homopolymer	None	None	None	10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Propane-1,2-diol	None	None	10 mg/m3 TWA Aerosol.	None
1-Acetyl-2-phenylhydrazine	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
N,N'-Ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). Use NIOSH approved respirator if there is potential to exceed

exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety show ers and eye wash stations should be available. Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash

stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene gloves. Use chemical resistant, impermeable clothing including gloves and either an apron or body

suit to prevent skin contact. Neoprene gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid, high viscosity

Color: Yellow Odor: Mild

Odor threshold:Not available.pH:Not available.Vapor pressure:Not available.Boiling point/range:Not available.Melting point/range:Not available.Specific gravity:1.17

Vapor density: Not available.

Flash point: > 93 °C (> 199.4 °F) no method

Flam mable/Explosive limits - low er: Not available. Flam mable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flam mability: Not applicable Evaporation rate: Not available. Solubility in water: Not available. Partition coefficient (n-octanol/water): Not available. **VOC** content: < 3 % Estimated Viscosity: Not available.

Viscosity: Not available.

Decomposition temperature: Not available.

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

Hazardous decomposition

products:

Oxides of carbon. Irritating organic vapours. Acids. Toxic fluorine compounds.

**Incompatible materials:** Strong oxidizing agents. Strong reducing agents. Free radical initiators. Inert gases. Oxygen

scavengers. Heavy metals. Alkalis. Aldehydes. Amines.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

#### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

## Potential Health Effects/Symptoms

Inhalation of vapors or mists of the product may be irritating to the respiratory system. Inhalation:

Skin contact: Causes skin irritation. May cause allergic skin reaction.

Eye contact:

Causes serious eye irritation.

May cause gastrointestinal tract irritation if sw allowed. Ingestion:

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Tetramethylene dimethacrylate	None	Irritant, Allergen
Oleic acid 5.5EO	None	Irritant
Methacrylic acid, monoester w ith 1,2- propanediol, polymer w ith 4,4'- methylenediphenyl diisocyanate	None	Irritant, Allergen
Polyglycol dimethacrylate	None	Irritant, Allergen
Ethene, homopolymer	None	No Target Organs
Ethene, tetrafluoro-, homopolymer	None	No Target Organs
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
Propane-1,2-diol	Oral LD50 (Rabbit) = 18 g/kg Oral LD50 (Mouse) = 23.9 g/kg Oral LD50 (Rat) = 30 g/kg	Irritant
1-Acetyl-2-phenylhydrazine	Oral LD50 (Mouse) = 270 mg/kg	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity
Cumene hydroperoxide	Inhalation LC50 (Mouse, 4 h) = 200 mg/l	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Tetramethylene dimethacrylate	No	No	No
Oleic acid 5.5EO	No	No	No
Methacrylic acid, monoester w ith 1,2- propanediol, polymer w ith 4,4'- methylenediphenyl diisocyanate	No	No	No
Polyglycol dimethacrylate	No	No	No
Ethene, homopolymer	No	No	No
Ethene, tetrafluoro-, homopolymer	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Propane-1,2-diol	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No
Cumene hydroperoxide	No	No	No
N,N'-Ethane-1,2-diylbis(12- hydroxyoctadecan-1-amide)	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
None
Packing group:
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
None
Packing group:
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division:

Identification number:

None
Packing group:

None

### 15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

nventory.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 10/12/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising fromsale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 2068748 Product name: LOCTITE 577 TTL 250ML US