

Loctite®
Superflex® SpeedSeal™
Silicone Sealant

**WATER-
RESISTANT**

**12X
FASTER**

than traditional sealants

LOCTITE®





Loctite® Superflex® SpeedSeal™ is a 1-component, fast-dry RTV silicone that withstands water contact just 2 hours after application. This 100% silicone rubber sealant replaces traditional sealants that require a minimum 24 hours prior to water exposure. Resistant to mold and mildew, this product features a flexible, watertight seal that provides a time-saving, back-in-service option.

FEATURES:

- 100% silicone formulation – no fillers
- Withstands water contact within 2 hours of application
- Creates a watertight, mold- and mildew-resistant seal
 - A “0” antimicrobial rating as tested per EN ISO 846
- Withstands temperature extremes of -30°F to 250°F
- Highly resistant to ultraviolet light and other environmental elements

APPLICATIONS:

Forms a weatherproof bond to materials like glass, ceramic, aluminum, primed steel and some plastics.

Typical applications include:

- Sealing bathtubs, sinks, fixtures, showers, etc.
- Applications where mildew is problematic



LOCTITE® SUPERFLEX® SPEEDSEAL™ SILICONE

ITEM #	COLOR	PACKAGE	CHEMISTRY BASE	CONSISTENCY	SERVICE TEMP.	SEALING TIME
1311327	Clear	300 ml cartridge	Acetoxy Silicone	Lump-free Paste	-30°F to 250°F (-34°C to 121°C)	Tack-free: 10 min.
1312042	White					Water-resistant: 2 hrs. Full Strength: 24 hrs.

Henkel Corporation
Engineering Adhesives
www.henkelna.com/mro
www.loctite.com

U.S.A.

Henkel Corporation
 Engineering Adhesives
 One Henkel Way
 Rocky Hill, Connecticut 06067
 Tel: 1.800.LOCTITE (1.800.562.8483)
 Tel: 860.571.5100
 Fax: 860.571.5044

Canada

Henkel Canada Corporation
 Engineering Adhesives
 2225 Meadowpine Blvd.
 Mississauga, Ontario L5N 7P2
 Tel: 1.800.263.5043 (within Canada)
 Tel: 905.814.6511
 Fax: 905.814.5391