

Quality Products. Service Excellence.

Type 4X Sloped Top Stainless Steel Freestanding 2STFS Series



Inner Panel Included









Application

- Designed to enclose electrical and/or electronic equipment and protect against harsh, industrial environments for larger applications.
- 20° sloped top prevents water from resting on top of enclosure.

Standards

- UL 508A Type 3R, 12, 4, 4X
- CSA Type 3R, 12, 4, 4X
- Complies with
 - NEMA Type 3R, 12, 13, 4, 4X
 - o IEC 60529, IP66
- · Appropriate components are required to maintain these standards.

Construction

- Formed from 12 gauge 304 or 316L stainless steel with smooth, continuously welded seams
- Flange trough collar (FTC) around door opening excludes liquids and contaminants.
- · Heavy duty lifting eyes are anchored into reinforced top corners.
- Removable doors are secured with bullet style, heavy duty, lift off hinges.
- Formed 10 gauge steel inner panel is provided on collar studs.
- Panel supports are provided.
- Center post is removable, providing easy panel installation.
- Heavy duty three point latching mechanism with heavy duty roller ends is provided for ease of door closing.
- · Seamless poured-in place gasket.
- Stainless steel door handles complete with padlock hasp.
- · A provision for mounting fluorescent lighting is provided.
- A bonding stud is provided in the door and a grounding stud is provided in the enclosure for each door.
- A literature pocket is provided for the inside of the door.

Finish

- Door and enclosure are natural stainless steel with a smooth, brushed finish..
- · Inner panel is finished in white powder coating.

Accessories

- Wash Down Floor Stand Kit
- Window Kits
- Lighting

- · Door Stop Kit
- Climate Control
- General Accessories

New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

304 S.S.	316 S.S.		Enclosure				Panel	
Part Number	Part Number	H1	H2	W	D	Н	W	
2STFS747512SS	2STFS747512S16	74.13	79.49	75.13	12.13	68.00	68.00	
2STFS747518SS	2STFS747518S16	74.13	79.49	75.13	18.13	68.00	68.00	
2STFS747524SS	2STFS747524S16	74.13	79.49	75.13	24.13	68.00	68.00	

Data subject to change without notice

© 2019. Hammond Manufacturing Ltd. All rights reserved.