ISSUE DATE: 06/26/2014 ----6.72[170.69] -> 3.94 100 .56 14.30 -OPTIONAL BACK PANEL SHOWN 0.100 [2.54mm] TH'K- ALUMINUM 0.075 [1.91mm] TH'K- WHITE STEEL .88[22.23] (2) POLYCARBONATE FLANGES (GLUED) (4) EACH #10-32 BRASS-INSERTS, AND STAINLESS STEEL FLANGE AND FEET SCREWS 6.50 165.10 -.10 2.54 -4.06 103.02 **BACK VIEW** 7.63 [193.79] -6.75 171.44 → 5.19 [131.75] ← STAINLESS STEEL 6.88 174.74 **HINGE PIN** SLOT MAX DIST SLOT DIST FRONT VIEW
WITH COVER REMOVED
AND BACK PANEL DISPLAYED 8X R.170 4.32 --4.00 101.60 CLOSED CELL NEOPRENE GASKET 4.81 122.24 -STAINLESS STEEL LOCKABLE SNAP LATCH LOCATED ON CENTER 4.25 107.95 4.81 122.24 .14 3.68 6.03 [153.29] -(4) EACH #10-32 BRASS INSERTS AND PLATED CARBON STEEL SCREWS WITH WASHERS >4.25[107.95]

6.26 [159.01]



