

RC2000 Series

Multi-Function Air Switches with 24-Hour Timer

- Remote control for one or two separate loads
- Multiple ON/OFF settings per day
- Flexible airhose enables operation up to 75 feet
- Type 3R plastic Indoor/Outdoor enclosure

Model #	Description	Switch	Input Voltage
G. RC2123PT	Timer with ON/OFF or HIGH/LOW	SPDT	120/240 VAC, 60 HZ
RC2343PT	2-circuit timer with sequential operations	4-function	120/240 VAC, 60 Hz

Rating:

Switch Rating: 20 A Resistive, 120, 240 VAC, 1 HP, 120 VAC, 2 HP, 240 VAC, each circuit

Enclosure Dimensions: 9 5/8" (23.82 cm) H x 5 1/2" (13.97 cm) W x 3 3/4" (9.53 cm) D

Warranty: 1 year



G.

RC2100 Series

Air Switch Control System

- Controls pool/spa combos
- Heater control
- Override timer for spa mode
- (2) PE24VA 24-volt valve actuators
- Heavy-duty Type 3R steel Indoor/Outdoor load center

Model #	Remote Command	Input Voltage
H. RC2163BE	1-Air Button	120/240 VAC
RC2163BFE	Any SPST switch*	120/240 VAC

*Sold separately

Rating:

Load Center Rating: 100 A, 120, 240 VAC or 120, 208 VAC single phase, 60 Hz.

Filter Pump:

Single Speed Only: 1.5 HP - 120 VAC, 3 HP - 240 VAC

Single or Two Speed: 1 HP - 120 VAC, 2 HP - 240 VAC

Breaker Spaces: 8/16

Number of Actuator Connections: 3

Load Center Dimensions:

16 1/2" (41.9 cm) H x 10 7/8" (27.6 cm) W x 4 1/4" (10.8 cm) D

Warranty: 1 year



H.

For replacement parts, trippers and accessories, see page 153.