



UPC Code: 078477740880
Country Of Origin: Mexico

MT562-1CT

Lev-Lok Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Split-Circuit, One Outlet Marked "Controlled", Tamper-Resistant, Smooth Face, 15 Amp, 125 Volt, Modular, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Light Almond

Mating Lev-Lok Wiring Module Required for Use

The Lev-Lok® Modular Wiring Device System is engineered for fast and easy installation. These devices employ a simple twist and lock wiring module that ensures a safe, reliable connection while at the same time providing for extremely fast and easy installation. Lev-Lok brand wiring devices address the reliability and performance concerns of specification engineers without sacrificing the contractor's need for fast, easy installation.

Technical Information

Product Features
Brand: Lev-Lok
Color: Light Almond

Controlled Outlets: 1

Device Type: Duplex Receptacle Outlet **Feature:** Split-circuit, One Outlet Marked

Controlled

Feature 2: Tamper-Resistant
Feature 4: Smooth Face
Grade: Heavy-Duty Industrial

Specification Grade

Horsepower Rating: 1/2 HP

AC Horsepower Ratings

Amperage: 15 A

Current Interrupting: Certified for current interrupting at full rated current

Dielectric Voltage: Withstands 2000V

per UL498

Grounding: Self-Grounding **Horsepower Rating:** 1/2 HP

Pole: 2

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 VAC

Wire: 3

Electrical Specifications

Amperage: 15 A

Current Interrupting: Certified for current interrupting at full rated current

Dielectric Voltage: Withstands 2000V

per UL498

Flammability: Rated V-2 per UL 94 Grounding: Self-Grounding

Operating Temperature: -40°C to 60°C

Pole: 2

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 VAC

Wire: 3

Ground Clips: Brass

Line Contacts: 0.040" Thick Solid Brass

Locking Pins: Solid Brass

Mounting Screws: Triple Combination

Head, Steel

Mounting Strap: Galvanized Steel
Operating Temperature: -40°C to 60°C

Shutter Mechanism: Acetal

Material Specifications
Base Material: Nylon
Bushing: Solid Brass
Cover Material: Nylon
Ground Clips: Brass

Line Contacts: 0.040" Thick Solid Brass

Locking Pins: Solid Brass

Mounting Screws: Triple Combination

Head, Steel

Mounting Strap: Galvanized Steel
Product ID: Ratings are permanently
marked on device

Shutter Mechanism: Acetal

Termination: Modular

Mechanical Specifications

Brand: Lev-Lok
Color: Light Almond

Device Type: Duplex Receptacle Outlet **Feature:** Split-circuit, One Outlet Marked

Controlled

Feature 2: Tamper-Resistant Feature 4: Smooth Face Grade: Heavy-Duty Industrial

Specification Grade

Product ID: Ratings are permanently marked on device

Termination: Modular

Standards and Certifications

ANSI: C-73

CSA C22.2 No. 42: File 152105

Environmental Specifications

Base Material: Nylon Bushing: Solid Brass Cover Material: Nylon

Flammability: Rated V-2 per UL 94

NOM: 057

UL Fed Spec WC-596: File E13399

UL498: File E13399 **Warranty:** 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:thm:condition} \textbf{Telephone: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

