



Color: Yellow

UPC Code: 07847707513

Country Of Origin: Mexico

NEMA:
L17-30R



69W77

Brand Features

Leviton's Wetguard line of industrial watertight wiring devices are the most versatile, well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive brands.

Item Description

Single Locking Receptacle, 30A, 600V 3 Phase, 3-Pole, 4-Wire, NEMA L17-30, Back and Side Wired, Corrosion-Resistant Yellow Cover - BLACK

Technical Information

AC Horsepower Ratings

At Rated Voltage: 10 HP

Electrical Specifications

Current Limiting: Full Rated Current

Dielectric Voltage: Withstands 2000V per UL498

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications

Environment: Wet

Flammability: Rated V-0 per UL 94

Operating Temperature: -40°C to 60°C

Material Specifications

Base Material: Nylon

Face Material: Nylon

Grounding Screw: Brass 8-32

Line Contacts: Brass .040 Thick

Terminal Screws: Brass 10-32

Yoke: Nickel-Plated Brass .050 Thick

Mechanical Specifications

Product ID: Ratings and NEMA I.D. permanently marked on device

Terminal Accom.: 14-8 AWG

Terminal ID: Brass-Hot, Green-Ground, White-Neutral

Product Features

Amperage: 30 A

Base Material: Nylon

Brand: Wetguard

Color: Yellow

Face Material: Nylon

Grounding: Grounding

NEMA: L17-30R

Pole: 3

Standards and Certifications: UL/CSA

Strap Material: Nickel-Plated Brass

Termination: Back

Voltage: 600 VAC

Warranty: Lifetime Warranty

Wire: 4

Device Type: Locking Outlet

Standards and Certifications

ANSI: C-73

CSA C22.2 No. 42: File LR-406

NEMA: WD-6

NOM: 057

UL498: File E13399

UL Fed Spec WC-596: File E13399

Technical drawing of the LEVATOR 400-12 power supply unit showing dimensions:

- Total height: 4.63 (117.5 mm)
- Height from base to top mounting holes: 3.25 (82.6 mm)
- Width between side mounting holes: 1.88 (47.6 mm)
- Total width: 3.13 (79.4 mm)

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

