
5461-IG





UPC Code: 07847766225

Country of Origin: Mexico - *Eligible for ARRA funded projects > \$7,443,000





Straight Blade Wiring Devices

Brand Features

Leviton's line of Extra Heavy-Duty Industrial Grade receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

Item Description

20 Amp, 250 Volt, NEMA 6-20R, 2P, 3W, Isolated Ground, Industrial Series Heavy Duty Specification Grade, Single Receptacle, Straight Blade, Self Grounding, Back & Side Wired, Steel Strap - ORANGE

Technical Information

AC Horsepower Ratings At Rated Voltage: 2 HP

Electrical Specifications

Grounding: Self-Grounding Amperage: 20 Amp Voltage: 250 Volt NEMA: 6-20R Pole: 2 Wire: 3 Dielectric Voltage: Withstands 2000V per UL498

Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications

Flammability: Rated V-2 per UL94 Operating Temperature: -40C to 60C

Material Specifications

Face Material: Thermoplastic Nylon Body Material: Thermoplastic Nylon Terminal Screws: Brass 10-32 Grounding Screw: Brass 8-32 Clamp Nuts: Zinc-Plated Steel Ground Clips: Brass-Plated Face Material: Nylon Body Material: Nylon Line Contacts: Brass Triple-Wipe Terminal Screws: Plated Brass Grounding Screw: Plated Steel Strap Material: Zinc-Plated Steel Clamp Nuts: Galvanized Steel Ground Clips: Brass Color: Orange Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground, White-Neutral

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 14-10 AWG **Product ID:** Ratings are permanently marked on device

Torque Range: 14-16 inch pounds

Product Features

Grounding: Isolated Ground NEMA: 6-20R Face Material: Thermoplastic Nylon Body Material: Thermoplastic Nylon Color: Orange

Standards and Certifications

NEMA: WD-6 ANSI: C-73 UL498: File E13399 UL Fed Spec WC-596: File E13399 CSA C22.2 No. 42: File 152105 NOM: 057 Warranty: 10 Year Limited



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc. 201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd. 165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 · FAX: 1-800-824-3005 www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2012-2015 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

*Buy American Compliant Logo -- The American Recovery And Reinvestment Act of 2009 ("ARRA") provides federal grants and loans for projects throughout the country. Section 1605 of the Act, named the "Buy American" provision, requires that certain materials and manufactured products used in projects funded by the Act be manufactured in the United States. The appearance of the Recovery Act Logo in relation to a Leviton product is only intended to reflect that such product may be used in an ARRA funded project. It does not mean that such product or Leviton is sponsored or endorsed by, or that Leviton receives funds from, the federal government or the Recovery Accountability and Transparency Board. Nothing in Leviton's use of the logo is intended to suggest anything regarding the requirements for funding under ARRA.

