



**Color:** Yellow

**UPC Code:** 07847707513

**Country Of Origin:** Mexico

**NEMA:**  
L17-30R



## 69W77

Single Locking Receptacle, 30A, 600V 3 Phase, 3-Pole, 4-Wire, NEMA L17-30, Back and Side Wired, Corrosion-Resistant Yellow Cover - BLACK

Leviton's Wetguard line of industrial watertight wiring devices are the most versatile, well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive brands.

### Technical Information

#### AC Horsepower Ratings

**At Rated Voltage:** 10 HP

#### Electrical Specifications

**Current Limiting:** Full Rated Current

**Dielectric Voltage:** Withstands 2000V per UL498

**Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current

#### Environmental Specifications

**Environment:** Wet

**Flammability:** Rated V-0 per UL 94

**Operating Temperature:** -40°C to 60°C

#### Material Specifications

**Base Material:** Nylon

**Face Material:** Nylon

**Grounding Screw:** Brass 8-32

**Line Contacts:** Brass .040 Thick

**Terminal Screws:** Brass 10-32

**Yoke:** Nickel-Plated Brass .050 Thick

#### Mechanical Specifications

**Product ID:** Ratings and NEMA I.D. permanently marked on device

**Terminal Accom.:** 14-8 AWG

**Terminal ID:** Brass-Hot, Green-Ground, White-Neutral

#### Product Features

**Amperage:** 30 A

**Base Material:** Nylon

**Brand:** Wetguard

**Color:** Yellow

**Face Material:** Nylon

**Grounding:** Grounding

**NEMA:** L17-30R

**Pole:** 3

**Standards and Certifications:** UL/CSA

**Strap Material:** Nickel-Plated Brass

**Termination:** Back

**Voltage:** 600 VAC

**Warranty:** Lifetime Warranty

**Wire:** 4

**Device Type:** Locking Outlet

#### Standards and Certifications

**ANSI:** C-73

**CSA C22.2 No. 42:** File LR-406

**NEMA:** WD-6

**NOM:** 057

**UL498:** File E13399

**UL Fed Spec WC-596:** File E13399

Technical drawing of the LEVATOR 6000 power supply unit showing dimensions:

- Total height: 4.63 (117.5 mm)
- Height from base to top mounting holes: 3.25 (82.5 mm)
- Width between side mounting holes: 1.88 (47.6 mm)
- Total width: 3.13 (79.4 mm)

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

