



ISOSTATIC
LEADERS IN BRONZE BEARINGS...and MORE

Isostatic Industries, Inc.
4153 North Kostner Avenue
Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 601302, Oilube® Powdered Metal Bronze SAE841 Sleeve Bearings / Bushings - METRIC

Isostatic Oilube® Bearings / Bushings

- Standard stock products
- SAE 841-copper (87-90%), tin (8-9), carbon, other elements
- Powdered metal bronze providing interconnected reservoirs for oil
- Vacuum impregnated with SAE 30 oil during the manufacturing process (approx. 19% by vol.)
- Self-lubricating – when in motion oil rises to the surface for lubrication and restores itself when at rest
- Ideal for heavy loads at moderate speeds or light loads at high speeds – max Pv 50,000, P-Load 2,000, V-SFM-1,200
-

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

20 MM I.D. x 25 MM O.D. x 22 MM Length, SAE 841 Powdered Metal Bronze, Sleeve Bearing, Metric

Specifications

Catalog Number	AM-2025-22
Interchange #	20-25x22
Unit of Measure	Each
Material	Powdered Metal / Oil Impregnated Bronze
Material Standard	SAE 841

Avg Unit Weight	0.0566 lb
UPC Code	00846802061449

Dimensions

Nominal Inner Diameter	20 mm
Nominal Outer Diameter	25 mm
Nominal Length	22 mm

Tolerances

Inner Diameter Tolerance	+0.005 to +0.03 mm
Outside Diameter Tolerance	+0.035 to +0.06 mm
Overall Length Tolerance	±.12 mm

Performance Data

Load - P Max Value	2,000 lb/in ²
Speed - V Max Value	1,200 ft ² /min
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	50,000