




Isostatic Industries, Inc.
 4153 North Kostner Avenue
 Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 102909, Oilube® Powdered Metal Bronze SAE841 Rectangular Plates - INCH

Isostatic Oilube® Rectangular Plates

- Standard stock products
- SAE 841-copper (87-90%), tin (8-9%), carbon, other elements
- Powdered metal bronze providing interconnected reservoirs for oil
- Vacuum impregnated with oil during the manufacturing process (approx. 19% by vol.)
- Self-lubricating – when in motion oil rises to the surface for lubrication and restores itself when at rest
- Ideal for heavy loads at moderate speeds or light loads at high speeds – max Pv 50,000, P-Load 2,000, V-SFM-1,200
-



[+ more](#)

[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

1/8 IN Thk. x 5 IN Wide x 6 IN Length, SAE 841 Powdered Metal Bronze, Flat Plate Stock

Specifications

Catalog Number	PP-6000
Interchange #	PP 6000 PP6000
Unit of Measure	Each
Material	Powdered Metal / Oil Impregnated Bronze
Material Standard	SAE 841

Avg Unit Weight 0.9543 lb

UPC Code 00846802012106

Dimensions

Nominal Length 6 in

Nominal Width 5 in

Nominal Plate Thickness 1/8 in

Tolerances

Overall Length Tolerance Oversized - to finish to

Width Tolerance Oversized - to finish to

Plate Thickness Tolerance ±.010 in

Performance Data

Load - P Max Value 2,000 lb/in²

Speed - V Max Value 1,200 ft²/min

Load at Speed - PV Max Value (P.S.I. / S.F.M.) 50,000