



ISOSTATIC
LEADERS IN BRONZE BEARINGS...and MORE


Isostatic Industries, Inc.
4153 North Kostner Avenue
Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 702028, TU® Steel-Backed PTFE Lined Flange Bearings - METRIC

Isostatic TU® Flange Bearings

- Standard stock products
- Self-lubricating dry sliding bearing
- A steel-backed composite material comprised of:
 - Low carbon steel backing for extremely high load capacity-.50 – 2.7mm thick
 - Sintered bronze offers optimal heat dispersion –.20 - .35 mm thickness and
 - PTFE – lead sliding surface creates a low friction coefficient and allows for a wide temperature range – thickness .2 mm
- Can be used where many liquid lubricants fail; also performs well with

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

25 MM I.D. x 28 MM O.D. x 11.5 MM Length, TU, Steel Back, PTFE & Pb Lined Composite, Flange Bearing, Metric

Specifications

Catalog Number	FM2511.5TU
Interchange #	BB2512DU FMB2511.5DU PAF 25115 P10
Unit of Measure	Each
Material	Steel-Backed PTFE Lined

Material Standard	Steel-Backed PTFE Lined
--------------------------	-------------------------

Avg Unit Weight	0.029 lb
------------------------	----------

UPC Code	00846802071271
-----------------	----------------

Dimensions

Nominal Inner Diameter	25 mm
-------------------------------	-------

Nominal Outer Diameter	28 mm
-------------------------------	-------

Nominal Length	12 mm
-----------------------	-------

Flange Nominal Outer Diameter	35 mm
--------------------------------------	-------

Flange Nominal Thickness	1.5 mm
---------------------------------	--------

Recommended Housing Bore	28.000 to 28.021 mm
---------------------------------	---------------------

Recommended Shaft Size	24.959 to 24.980 mm
-------------------------------	---------------------

Tolerances

Overall Length Tolerance	±.25 mm
---------------------------------	---------

Flange Diameter Tolerance	±.50 mm
----------------------------------	---------

Flange Thickness Tolerance	1.30 to 1.50 mm
-----------------------------------	-----------------

Performance Data

Load - P Max Value	36,250 lb/in ²
---------------------------	---------------------------

Speed - V Max Value	1,900 ft ² /min
----------------------------	----------------------------

Load at Speed - PV Max Value (P.S.I. / S.F.M.)	102,000
---	---------