

General Properties of SBR†

- Good physical properties.

† Properties shown based on Rubber Manufacturers Association Sheet Rubber Handbook, second edition.

NEW
ITEMS

RED SBR SHEET

Plate
Finish

Fabric
Finish

SPECIFICATIONS:

Commercial grade red SBR sheet, Plate or Fabric Finish:

Style R75: 70 Duro hardness (Shore Durometer A)

Style RF75: 70 Duro hardness (Shore Durometer A)

Polymer: Styrene-Butadiene

Common Name: Red Rubber Sheet

ISO/ASTM Designation: SBR

Meets D1330 Grade 1

Talc Free

Style	ASTM Specification (SI units)	Temp. Range	Durometer	Tensile Strength (PSI)	Elongation (%)	Finish
R75	D 2000 M1AA 705	-22°F to +158°F	65 – 75	600	200%	Plate
RF75	D 2000 M1AA 705	-22°F to +158°F	65 – 75	600	200%	Fabric Impression

ORDERING INFORMATION:

Item Number		Gauge x Width (in.)	Avg. Length (Linear Ft./Roll)	Approx. Lbs./Roll
Plate Finish	Fabric Impression			
R75-02x36x67	RF75-02x36x67	1/16 x 36	67	106
✓ R75-02x72x67		1/16 x 72	67	212
R75-04x36x36	RF75-04x36x36	1/8 x 36	36	114
R75-04x36x50		1/8 x 36	50	158
✓ R75-04x72x36		1/8 x 72	36	228
R75-06x36x36	RF75-06x36x36	3/16 x 36	36	171
R75-08x36x18	RF75-08x36x18	1/4 x 36	18	114
R75-08x36x25		1/4 x 36	25	158
R75-08x36x50		1/4 x 36	50	316
R75-02x48x67	RF75-02x48x67	1/16 x 48	67	141
R75-03x48x67	RF75-03x48x67	3/32 x 48	67	211
R75-04x48x36	RF75-04x48x36	1/8 x 48	36	152
R75-04x48x50		1/8 x 48	50	211
R75-06x48x36	RF75-06x48x36	3/16 x 48	36	228
R75-08x48x18	RF75-08x48x18	1/4 x 48	18	152
R75-08x48x25		1/4 x 48	25	211
R75-08x48x50		1/4 x 48	50	422

