

UltraLED™ Volumetric Troffer



UltraLED™ Volumetric Troffer

Key Features and Benefits



- All models are **125+ LPW**, **DLC Premium** listed to maximize rebate opportunities and offer 0-10V dimming to optimize energy savings
- These are ideal in replacing traditional acrylic or parabolic fluorescent troffers offering up to **59% energy savings**
- Offered in two wattage/lumen packages, three color temperatures, and two voltage ranges (120-277 and 120-347)
- **100,000 hour rated life**

Applications

- Offices
- Educational
- Residential
- General Lighting

Volume3A				
Wattage	CCT (K)	Dimming	Voltage	Warranty
26 34	3500K, 4000K, 5000K	0-10	120-277 (UNV) 120-347 (UNH)	5 years

UltraLED™ Volumetric Troffer

Product Offering (Stock)

Item Number	Ordering Abbreviation	Power (W)	Input Voltage	Dimming	CRI	Color Temp	Lumens	Lumens Per Watt	DLC Listed	Options
60878	VOLUME4A/034UNVD835/24G/WH	34	120-277	0-10	>80	3500 K	4250	125	Prm	-
60879	VOLUME4A/034UNVD840/24G/WH	34	120-277	0-10	>80	4000 K	4250	125	Prm	-
60880	VOLUME4A/034UNVD850/24G/WH	34	120-277	0-10	>80	5000 K	4250	125	Prm	-
60869	VOLUME4A/026UNVD835/22G/WH	26	120-277	0-10	>80	3500 K	3250	125	Prm	-
60870	VOLUME4A/026UNVD840/22G/WH	26	120-277	0-10	>80	4000 K	3250	125	Prm	-
60871	VOLUME4A/026UNVD850/22G/WH	26	120-277	0-10	>80	5000 K	3250	125	Prm	-

UltraLED™ Volumetric Troffer

Product Offering (MTO)



Item Number	Ordering Abbreviation	Power (W)	Input Voltage	Dimming	CRI	Color Temp	Lumens	Lumens Per Watt	DLC Listed	Options
60884	VOLUME4A/034UNVD835/24G/WH/D	34	120-277	0-10	>80	3500 K	4250	125	Prm	Sensor
60885	VOLUME4A/034UNVD840/24G/WH/D	34	120-277	0-10	>80	4000 K	4250	125	Prm	Sensor
60886	VOLUME4A/034UNVD850/24G/WH/D	34	120-277	0-10	>80	5000 K	4250	125	Prm	Sensor
60875	VOLUME4A/026UNVD835/22G/WH/D	26	120-277	0-10	>80	3500 K	3250	125	Prm	Sensor
60876	VOLUME4A/026UNVD840/22G/WH/D	26	120-277	0-10	>80	4000 K	3250	125	Prm	Sensor
60877	VOLUME4A/026UNVD850/22G/WH/D	26	120-277	0-10	>80	5000 K	3250	125	Prm	Sensor
60857	VOLUME4A/034UNVD835/24G/WH/E	34	120-277	0-10	>80	3500 K	4250	125	Prm	Emergency
60858	VOLUME4A/034UNVD840/24G/WH/E	34	120-277	0-10	>80	4000 K	4250	125	Prm	Emergency
60859	VOLUME4A/034UNVD850/24G/WH/E	34	120-277	0-10	>80	5000 K	4250	125	Prm	Emergency
60863	VOLUME4A/026UNVD835/22G/WH/E	26	120-277	0-10	>80	3500 K	3250	125	Prm	Emergency
60864	VOLUME4A/026UNVD840/22G/WH/E	26	120-277	0-10	>80	4000 K	3250	125	Prm	Emergency
60865	VOLUME4A/026UNVD850/22G/WH/E	26	120-277	0-10	>80	5000 K	3250	125	Prm	Emergency
60860	VOLUME4A/034UNVD835/24G/WH/DE	34	120-277	0-10	>80	3500 K	4250	125	Prm	Sensor, Emergency
60861	VOLUME4A/034UNVD840/24G/WH/DE	34	120-277	0-10	>80	4000 K	4250	125	Prm	Sensor, Emergency
60862	VOLUME4A/034UNVD850/24G/WH/DE	34	120-277	0-10	>80	5000 K	4250	125	Prm	Sensor, Emergency
60866	VOLUME4A/026UNVD835/22G/WH/DE	26	120-277	0-10	>80	3500 K	3250	125	Prm	Sensor, Emergency
60867	VOLUME4A/026UNVD840/22G/WH/DE	26	120-277	0-10	>80	4000 K	3250	125	Prm	Sensor, Emergency
60868	VOLUME4A/026UNVD850/22G/WH/DE	26	120-277	0-10	>80	5000 K	3250	125	Prm	Sensor, Emergency
60881	VOLUME4A/034UNHD835/24G/WH	34	120-347	0-10	>80	3500 K	4250	125	Prm	-
60882	VOLUME4A/034UNHD840/24G/WH	34	120-347	0-10	>80	4000 K	4250	125	Prm	-
60883	VOLUME4A/034UNHD850/24G/WH	34	120-347	0-10	>80	5000 K	4250	125	Prm	-
60872	VOLUME4A/026UNHD835/22G/WH	26	120-347	0-10	>80	3500 K	3250	125	Prm	-
60873	VOLUME4A/026UNHD840/22G/WH	26	120-347	0-10	>80	4000 K	3250	125	Prm	-
60874	VOLUME4A/026UNHD850/22G/WH	26	120-347	0-10	>80	5000 K	3250	125	Prm	-

UltraLED™ Volumetric Troffer

Nomenclature

VOLUME	4A/	XXX	UNX	D		8 XX/	XX	G/	WH/	
Product Name	Generation	Wattage	Voltage	Dimming	CRI	CCT	Dimension	Mounting	Color	Option
VOLUME	4A	026 = 26 Watts	UNV = 120-277V	D = 0-10V	8 = >80	35 = 3500K	22 = 2x2	G = Grid	WH = White	Blank = No option
		034 = 34 Watts	UNH = 120-347V			40 = 4000K	24 = 2x4			E = Emergency Back-up
						50 = 5000K				D = Daylight / Motion Sensor
										DE = Dual Emergency and Daylight / Motion Sensor

UltraLED™ Volumetric Troffer

Phase In – Phase Out

- VOLUME1A/2A will be phased out and have been turned stat 22 (discontinued with inventory)
- The ValueLED™ and UltraLED™ Volumetric Troffers are both active product families that will continue to be supported
- The Sensor, Emergency, and UNH versions of this product will be created in Kentucky leveraging existing LSOD processes



UltraLED™ Volumetric Troffer

Key Takeaways

- All models are DLC Premium listed to maximize rebate opportunities and offer 0-10V dimming to optimize energy savings
- These are ideal in retrofit applications offering up to 59% energy savings when compared to traditional lighting technologies
- Offered in two wattage/lumen packages, three color temperatures, and two voltage ranges (120-277 and 120-347)
- 100,000 hour rated life



THANK YOU