



Product Number: 64656

Order Abbreviation: MS360/C/SS/BU-HOR

General Description: 360W METALARC SUPERSAVER energy saving quartz metal halide lamp, high output, position dedicated, E39 base, BT37 bulb, enclosed fixture rated, coated, base up through horizontal burn, 3600K

Product Information

Abbrev. With Packaging Info.	MS360CSSBUHOR 6/CS 1/SKU
ANSI Code	M59/S:M165/S
ANSI Code 2	M165/S
Approx. Lumens (initial - horizontal)	30000
Approx. Lumens (initial - vertical)	35000
Approx. Lumens (mean - horizontal)	19000
Approx. Lumens (mean - vertical)	22500
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Average Rated Life - Vertical (hr)	20000
Base	E39 Mogul
Bulb	BT37
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3600
Diameter (in)	4.606
Diameter (mm)	117.00
Family Brand Name	Metalarc® Super Saver
Fixture Requirement	S
Hot Restrike Time (min)	7-12
Lamp Finish	Coated
Light Center Length - LCL (in)	7
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Voltage (V)	120.00
Nominal Wattage (W)	360.00
Operating Position	Base up through horizontal
Warm-up Time (min)	2-4

Footnotes

- Operates at 360 watts on 400w M59 ballast or a M165 ballast.
- S = When operated within 15 degrees of vertical, this lamp may be operated in an open luminaire provided the installation is not near people or flammable or combustible material, otherwise it must be operated in a suitably enclosed luminaire. See lamp warning.