

Product Number: 20590

Order Abbreviation: FT55DL/830/ECO

General Description: DULUX 55W long compact fluorescent lamp with 4-pin base, 3000K color temperature, 82 CRI, ECOLOGIC for use on magnetic, electronic and dimming ballasts



Product Information

Abbrev. With Packaging Info.	FT55DL830ECO 10/CS 1/SKU
Average Rated Life (hr)	12000
Base	2G11
Bulb	L (T5)
Color Rendering Index (CRI)	80 - 89
Color Temperature/CCT (K)	3000
Diameter (in)	0.709
Diameter (mm)	18.00
Family Brand Name	Dulux® L
Initial Lumens at 25C	4800
Mean Lumens at 25C	4128
Maximum Overall Length - MOL (in)	21.1
Maximum Overall Length - MOL (mm)	535
Nominal Wattage (W)	55.00



Footnotes

- Approximate initial lumens after 100 hours operation.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- There is a NEMA supported, industry issue where T2, T4, and T5 fluorescent and compact fluorescent lamps operated on high frequency ballasts may experience an abnormal end-of-life phenomenon. This end-of-life phenomenon can result in one or both of the following: 1. Bulb wall cracking near the lamp base. 2. The lamp can overheat in the base area and possibly melt the base and socket. NEMA recommends that high frequency compact fluorescent ballasts have an end-of-life shutdown circuit which will safely and reliably shut down the system in the rare event of an abnormal end-of-life failure mode described above. The final requirements of this system are yet to be defined by ANSI. For additional information refer to NEMA papers on their WEBSITE at www.NEMA.org.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Lumen output rated on high frequency operation. 60 HZ operation would result in lower lumen output.
- Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.