



UPC Code: 07847779707

Country Of Origin: Mexico



4760-IG

Brand Features

Leviton's line of Extra Heavy-Duty Industrial Grade locking receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

Item Description

15 Amp, 277 Volt, NEMA L7-15R, 2P, 3W, Single Locking Receptacle, Industrial Grade, Isolated Ground - ORANGE

Technical Information

AC Horsepower Ratings At Rated Voltage: 2 HP

Electrical Specifications Grounding: Isolated Ground

Amperage: 15 A Voltage: 277 VAC Pole: 2 Wire: 3 Dielectric Voltage: Withstands 2000V per UL498 Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C Environment: Dry

Material Specifications

Face Material: Nylon Body Material: Nylon Line Contacts: Brass .031 Thick Terminal Screws: Brass 10-32 Grounding Screw: Brass 8-32 Yoke: Zinc-Plated Steel Strap Material: Nickel-Plated Brass Color: Orange Mechanical Specifications Terminal ID: Brass-Hot, Green-Ground,

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 18-10 AWG

Product ID: Ratings and NEMA I.D. permanently marked on device Termination: Side

Product Features


NEMA: L7-15R Color: Orange Feature: Isolated Ground

_


Standards and Certifications NEMA: WD-6 ANSI: C-73 UL498: File E13399 UL Fed Spec WC-596: File E13399 CSA C22.2 No. 42: File LR-406 NOM: 057 Warranty: Lifetime Warranty



Dimensional Diagram



Wiring Diagram



L7-15R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

