



Product Number: 64716

Order Abbreviation: MP1000/C/BU-ONLY

General Description: 1000W METALARC PRO-TECH quartz metal halide lamp, EX39 base, BT56 bulb, open fixture rated, base up only, coated, 3400K

Product Information

Abbrev. With Packaging Info.	MP1000CBUONLY 6/CS 1/SKU
ANSI Code	M47/O
ANSI Code 2	M47/O
Approx. Lumens (initial - horizontal)	102000
Approx. Lumens (initial - vertical)	102000
Approx. Lumens (mean - vertical)	82000
Average Rated Life - Vertical (hr)	15000
Base	EX39 Exclusionary Mogul
Bulb	BT56
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3200
Diameter (in)	7.008
Diameter (mm)	178.00
Family Brand Name	Metalarc Pro-Tech®
Fixture Requirement	O
Hot Restrike Time (min)	10
Lamp Finish	Coated
Light Center Length - LCL (in)	9.5
Light Center Length - LCL (mm)	241
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	15.4
Maximum Overall Length - MOL (mm)	391
Nominal Voltage (V)	263.00
Nominal Wattage (W)	1000.00
Operating Position	Base up within 15deg only
Warm-up Time (min)	2-4

Footnotes

- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaires. See lamp warning.

