





UPC Code: 07847784815

Country Of Origin: United States

**NEMA**: 6-15R



# 1549

#### **Brand Features**

Leviton's Dustguard line of industrial grade plugs and connectors feature rugged construction that resists impact, sunlight, chemicals and rough use. All contacts are solid one-piece construction for superior conductivity. They are engineered to IP44 Splash proof and dust-tight standards. The ergonomic, fluted-body design with radial gripping edge is ideal for gripping and pulling. The unique cord clamp accepts a wide range of cord sizes, providing a secure grip without damaging the cord. And, they are backed by a limited lifetime warranty.

### **Item Description**

15 Amp, 250 Volt, NEMA 6-15R, 2P, 3W, Connector, Straight Blade, Industrial Grade, Grounding, Dustguard - YELLOW

#### **Technical Information**

Electrical Specifications

Amperage: 15 A

**Current Limiting:** Full Rated Current **Dielectric Voltage:** Withstands 2000V

per UL498

**Grounding:** Grounding

Pole: 2

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 250 VAC

Wire: 3

**Environmental Specifications** 

Environment: Dry

Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications

Assembly Screws: Steel, Zinc Plated Blades/Contacts: Solid Brass Body Material: Santoprene TPV Bushing: Santoprene TPV

Compression Nut, Strain Relief: Nylon

Terminal Screws: Brass Wire Module: Thermoplastic Mechanical Specifications
Cord Range: .375 - .655

**Product ID:** Ratings and NEMA I.D. permanently marked on device **Terminal Accom.:** 18-10 AWG

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Wire Gauge: 18-12 AWG

Product Features

Brand: Dustguard

Color: Yellow

Device Type: Straight Blade Connector

**NEMA:** 6-15R

Standards and Certifications

**ANSI:** C-73

CSA C22.2 No. 42: File LR-406

NEMA: WD-6 NOM: 057 UL: 498


UL Fed Spec WC-596: File E13393

Warranty: 2 Year Limited

## Dimensional Diagram



## Wiring Diagram



6-15R

### SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$ 

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

### Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

