



Color:  Grey

UPC Code: 07847710185

Country Of Origin: Mexico

## N3602

60 Amp, 600 Volt, Toggle In Type 3R Enclosure Double-Pole AC Manual Motor Controller, Industrial Grade, Non-Grounding, Front Wired, - Grey

Powerswitch® Industrial Grade AC Manual Motor Controllers provide safe, reliable control of a variety of motor loads. Typical applications include manual ON/OFF switching control of conveyor systems, pumping machines, HVAC systems, air compressors and other heavy manufacturing equipment. These motor controllers are available for both single-phase and three-phase applications.

### Technical Information

#### AC Horsepower Ratings

**HP Rating:** 10HP-240V 15HP-480V  
20HP-600V

#### Electrical Specifications

**Amperage:** 60 A

**Dielectric Voltage:** Withstands 2200V for 1 min.

**Endurance:** 6,000 cycles inductive motor type load

**Grounding:** Non-Grounding

**Overload UL20 Test:** 100 cycles of OL at 4.8 times rated current

**Pole:** 2

**Temperature Rise:** 50°C Max at full rated current

**Voltage:** 600 VAC

#### Environmental Specifications

**Enclosure Rating:** Type 3R

**Flammability:** Rated V-0 per UL 94

**Operating Temperature:** -40°C to 60°C

#### Material Specifications

**Base Material:** Thermoplastic Polyester

**Contacts:** .046" Thick Silver-Cadmium Oxide

**Enclosure Material:** Powder-Coated Steel

**Face Material:** Thermoplastic Polyester

**Handle Material:** Valox 357 PBT

**Strap Material:** Nickel Plated Brass

**Terminal Screws:** Zinc-Plated Steel, Triple Combination

**Toggle:** Thermoplastic Polyester

**Yoke:** Nickel-Plated Brass

#### Mechanical Specifications

**Product ID:** Ratings are permanently marked on device

**Terminal Accom.:** 10-4 AWG

**Terminal ID:** T1, T2, T3, L1, L2 & L3 marked on back of device

**Termination:** Front

**Torque Range:** 25 inch pounds maximum

#### Product Features

**Color:** Grey

**Device Type:** Manual Motor Controller

#### Standards and Certifications

**ANSI:** C-73

**cUL per CSA C22.2 No. 111:** File #E63969


**NEMA:** WD-1 & WD-6

**NOM:** NOM-ANCE


**tsa\_ul508:** File #E63969

**UL 60947-4-1:** supersedes UL 508

**Warranty:** 10-Year Limited



### Wiring Diagram Double Pole



### SPECIFICATION SUBMITTAL

|                      |                      |                      |
|----------------------|----------------------|----------------------|
| JOB NAME:            | CATALOG NUMBERS:     |                      |
| <input type="text"/> | <input type="text"/> | <input type="text"/> |
| JOB NUMBER:          | <input type="text"/> | <input type="text"/> |

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

