



Color :

White

UPC Code: 078477683866
Country Of Origin: China



## Available Colors :







Brown

wn



Ivory

Light Almond

# T5632-W

3.6A USB Type-A/Type-A Wall Outlet Charger with 15A Tamper-Resistant Receptacles

Combination Duplex Receptacle/Outlet and USB Charger. 15 Amp, 125 Volt, Decora Tamper-Resistant Receptacle/Outlet, NEMA 5-15R. 3.6 Amps, 5VDC, 2.0 Type A USB Chargers. Grounding, Side Wired & Back Wired - White

- SMART Built-in smart chip recognizes the individual device's charging requirement to optimize the charge
- POWERFUL Two high-powered charging ports with 3.6A of charging power
- CONVENIENT No more searching for charging adapters! Upgrade your existing outlets so you can charge up to two USB powered electronics at once, leaving the outlets free for additional power needs
- EASY Compact design fits in a standard wallbox and works with Decora and Decora Plus screwless wallplates.

#### **Technical Information**

Product Features
Amperage: 15 A
Brand: Decora

Grade: Residential/Commercial

Specification Grade

Grounding: Grounding

Horsepower Rating: 15A-1/2 HP

**NEMA:** 5-15R

Product Type: Outlet/USB Combo

Ratings: 15A-125V

Type: Type A/A Duplex Receptacle

Voltage: 125 VAC
Wallplate: Not Included
Electrical Specifications

Amperage: 15 A
Flammability: Rated V-0 per UL 94

**Grounding**: Grounding

Horsepower Rating: 15A-1/2 HP Operating Temperature: -10°C to 40°C

**Ratings**: 15A-125V

Environmental Specifications

**Body Material :** Thermoplastic

Color: White

Cover Material: Thermoplastic

Flammability: Rated V-0 per UL 94

Operating Temperature: -10°C to 40°C

Strap Material: Steel

Material Specifications

**Body Material:** Thermoplastic

Color: White

**Cover Material :** Thermoplastic **Product ID :** Stamped on Strap

Strap Material: Steel

Terminal Accom.: 14-12 AWG Terminal ID: Brass-Hot Black-Hot White-Neutral Green-Gnd

Termination: Back & Side

Torque Range: 12-14 inch pounds

Mechanical Specifications

Amperage: 15 A

Color : White

Grade: Residential/Commercial

Specification Grade

Product ID : Stamped on Strap Terminal Accom. : 14-12 AWG Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd

Termination: Back & Side

Torque Range: 12-14 inch pounds

Standards and Certifications

FCC Part 15 : Class B Listed : cCSAus NOM : 057 UL 1310 : Yes UL 498 : Yes

Warranty: 5-Year Limited

#### **Features and Benefits**

 Perfect for use in residential applications such as kitchens, bedrooms and home offices and in commercial applications such as hotels, airports, restaurants and cafes, salons, office cubicles and college dorm rooms

- Smart chip recognizes and optimizes the charging requirements of individual devices
- USB Ports are positioned vertically providing more space for maneuvering and reducing stress on USB cables
- Compatible with USB 3.0, 2.0, 1.1 devices
- Fits in a standard wallbox, is compatible with standard wallplates and can be multi-ganged with other devices
- Easy to install. Can replace existing outlets
- No data transfer capability
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates.

  Wallplate sold separately

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

## Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:thm:condition} \textbf{Telephone: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$ 

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

#### Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

# Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

