



Color:

Clear

UPC Code: 07847723944

1203-LHC

15 Amp, 120 Volt, Toggle Lighted Handle - Illuminated OFF 3-Way AC Quiet Switch, Industrial Grade, Self Grounding, Back & Side Wired, - Clear

Leviton's Industrial Grade AC toggle switches for extra heavy-duty applications represent top-of-the-line quality and peak performance. Leviton uses the finest materials available and the highest production standards to produce industrial switches of unmatched versatility and reliability.

Technical Information

AC Horsepower Ratings HP Rating: 1/2HP-120V Max. Amperage: 12 Amp

Electrical Specifications

Amperage: 15 A Voltage: 120 VAC Grounding: Self-Grounding Dielectric Voltage: Withstands 1500V for 1 minute Overload UL20 Test: 100 cycles of OL

at 4.8 times rated current

Temperature Rise: Maximum 30 degrees C rise

Endurance: 50,000 cycles minimum

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 65°C

Material Specifications Strap Material: Steel Base Material: Thermoplastic Toggle: Polycarbonate Cover Material: Thermoplastic Contact Material: Silver Alloy Terminal Screws: Brass 8-32 Grounding Screw: Brass 8-32 Ground Clips: Brass Color: Clear Mechanical Specifications

Terminal ID: Brass-Hot Black-Hot White-Neutral Green-Gnd Terminal Accom : 14-#10 AWG bac

Terminal Accom.: 14-#10 AWG back wired; #14-#12 AWG side wired

Product ID: Ratings are permanently marked on device

Torque Range: 12-14 inch pounds Termination: Back or Side Wire


Product Features
Color: Clear

Grounding: Self-Grounding Actuator Material: Polycarbonate Body Material: Thermoplastic Strap Material: Steel


Function: 3-Way Grade: Extra Heavy-Duty Industrial Specification Grade Feature 2: Illuminated - Load OFF Device Type: Toggle Switch

Standards and Certifications NEMA: WD-1 & WD-6 ANSI: C-73 UL Fed Spec WS896E: File #E7458 UL Standard: UL 20 CSA C22.2 No. 111: File #152105 NOM: 057 RoHS: Compliant Warranty: 10 Year Limited

Dimensional Diagram



Wiring Diagram 3-Way Lighted



SPECIFICATION SUBMITTAL

| JOB NAME: | CATALOG NUMBERS: | |
|-------------|------------------|--|
| | | |
| JOB NUMBER: | | |

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

