

6377CR



Color: **N/A** Gray Metal

UPC Code: 07847733299

Country Of Origin: Mexico

NEMA:
Non-NEMA



50 Amp, 125 Volt, Non-NEMA, 2P, 3W, Corrosion Resistant, Black & White Locking Flanged Inlet, Industrial Grade, Grounding, - GRAY METAL

Leviton Black & White 50Amp Non-NEMA Locking devices are designed for faster wiring and longer life. Made from tough, impact-resistant nylon housings and metal shrouds, these plugs, connectors, receptacles and flanged inlets are designed for rugged environments like construction sites, commercial shipyards and convention centers.

Technical Information

Electrical Specifications

Grounding: Grounding

Amperage: 50 A

Voltage: 125 VAC

Pole: 2

Wire: 3

Dielectric Voltage: Withstands 2000V per UL498

Maximum Working Voltage: 125V as rated

Temperature Rise: Max 30°C temp rise at full-rated current after 150 cycles of OL at 150% rated DC current

Current Interrupting: Certified for current interrupting at full rated current

Environmental Specifications

Flammability: Rated V-2 per UL 94

Operating Temperature: -40°C to 75°C

Environment: Corrosive

Material Specifications

Face Module: Nylon

Body & Contract Carrier: Reinforced Nylon

Flanged Casing: Zinc Plated Brass

Inlet Blade: 0.100inch thick Nickel Plated Brass

Terminal Block: 0.062inch thick Nickel Plated Copper

Terminal Set Screw: SS 302/304

Ground Shunt: Nickel Plated Bronze

Grounding Shunt Rivet: Nickel Plated Brass

Color: Gray Metal

Mechanical Specifications

Terminal ID: X, W, Y, Z and Green for ground

Terminal Accom.: #10 min to #4max AWG Solid or Stranded Wire

Product ID: Ratings and Catalogue No. molded into face

Product Features

NEMA: Non-NEMA

Color: Gray Metal

Brand: Black and White

Standards and Certifications

UL498: File E13399

CSA C22.2 No. 42: File 152105

NOM: 057

RoHS: Compliant

Warranty: Lifetime Limited

