




UPC Code: 07847724980

Country Of Origin: United States



5821-l

Single Receptacle Outlet, Commercial Specification Grade, Smooth Face, 20 Amp, 250 Volt, Side Wire, NEMA 6-20R, 2-Pole, 3-Wire, Self-Grounding - Ivory

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

Technical Information

AC Horsepower Ratings At Rated Voltage: 2 HP

Electrical Specifications Dielectric Voltage: Withstands 2000V

per UL498 Current Limiting: Full Rated Current Amperage: 20 A Grounding: Self-Grounding Pole: 2 Voltage: 250 VAC

Wire: 3

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C


Material Specifications Face Material: Nylon Body Material: Nylon Line Contacts: Brass Double Wipe .031 Thick Terminal Screws: Brass 8-32 Grounding Screw: Brass 8-32 Yoke: Zinc-Plated Steel Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground, White-Neutral


Terminal Accom.: 14-10 AWG Product ID: Ratings are permanently marked on device Termination: Side Wire **Product Features** Grounding: Self-Grounding Amperage: 20 A Voltage: 250 VAC **NEMA: 6-20R** Pole: 2 Wire: 3 Termination: Side Wire Face Material: Nylon Body Material: Nylon Strap Material: Steel Color: Ivory Standards and Certifications: UL/CSA Warranty: 10 Year Limited Device Type: Single Receptacle Outlet Feature 4: Smooth Face Grade: Commercial Specification Grade Standards and Certifications NEMA: WD-1 & WD-6 ANSI: C-73

UL498: File E13399 UL Fed Spec WC-596: File E13399 CSA C22.2 No. 42: File 152105 NOM: 057

Dimensional Diagram



Wiring Diagram



6-20R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30A)

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

