

4996-KIT



Weatherproof Kit Assembly Consisting of One Self-Test Tamper-Resistant, Weather-Resistant Slim GFCI Receptacle (GFTW1-GY); Lighted NEMA 5-15R, 15A-125V @ Receptacle, Grey w/ Grey Test and Reset Button, One Horizontal Outdoor Coverplate with Self-Closing Cover (4996-GY). One Aluminum Box (1GM53).

Weather-resistant kit including the following components in one easy to install package:

- One GFTW1-GY, 15 Amp, 125 Volt Receptacle, SmartlockPro weather & tamper-resistant GFCI in gray
- One 4996-GY, 1-Gang, Decora Weather-Resistant Cover with self-closing lid in gray
- One 1GM53-GY, 1-Gang Die-Cast Weatherproof Box with Three 1/2" Diameter threaded holes

UPC Code : 068679151508

Country Of Origin : China



Technical Information

Product Features

Brand : SmartlockPro

Color : Gray

Feature : Self-Test Receptacle, Self Closing Lid

Grade : Residential/Commercial Specification Grade

NEMA : 5-15R

Electrical Specifications

Amperage : 15 A

Dielectric Voltage : Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06

Grounding : Green Ground Screw

Pole : 2

Short Circuit Current Rating : 10KA

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Trip Level : Class A, 5mA plus or minus 1mA

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Operating Temperature : -35C to +66C

Material Specifications

Body Material : Polycarbonate

Face Material : Polypropylene

Grounding Screw : Stainless Steel

Line Contacts : Brass Double-Wipe .031 Thick

Tamper Resistant : Yes

Terminal Screws : Stainless Steel

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Termination : Back & Side

Wire : 3

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : Yes

CSA-C22.2 No. 144.1-06 : File LR-57811

Fed Spec WC-596 : Yes

MIL-SPEC : A-A-55459-SB

NOM : Yes

UL 943 : File E48380

UL498 : Yes

Cover Specifications

Color : Gray

Gang : 1

Material : Thermoplastic

Mount : Device

Orientation : Horizontal

Standards and Certifications : UL/CSA

Type : Standard Duplex, Weather Resistant

Warranty : 2-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

