




UPC Code: 07847777359

Country Of Origin: United States



5822

Brand Features

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

Item Description

Duplex Receptacle Outlet, Commercial Specification Grade, Indented Face, 20 Amp, 250 Volt, Side Wire, NEMA 6-20R, 2-Pole, 3-Wire, Self-Grounding - Brown

Technical Information

AC Horsepower Ratings At Rated Voltage: 2 HP

Electrical Specifications Grounding: Self-Grounding Amperage: 20 A Voltage: 250 VAC Pole: 2 Wire: 3 Dielectric Voltage: Withstands 2000V per UL498 Current Limiting: Full Rated Current Temperature Rise: Max 30C after 100 cycles OL at 150 percent rated current Environmental Specifications

Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications Body Material: Nylon

Face Material: Nylon Line Contacts: Brass Double Wipe .031 Thick Terminal Screws: Brass 8-32 Grounding Screw: Brass 8-32 Strap Material: Zinc-Plated Steel Ground Clips: Brass-Plated Color: Brown Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 14-10 AWG

Product ID: Ratings are permanently marked on device

Termination: Side Wire

Product Features

Grounding: Self-Grounding NEMA: 6-20R


Body Material: Nylon

Color: Brown Device Type: Duplex Receptacle Outlet Feature 4: Indented Face Grade: Commercial Specification Grade


Standards and Certifications

NEMA: WD-2 WD-6 ANSI: C-73 UL498: File E13399 UL Fed Spec WC-596: File E13399 CSA C22.2 No. 42: File 152105 NOM: 057 Warranty: 10 Year Limited

Dimensional Diagram



Wiring Diagram



6-20R

SPECIFICATION SUBMITTAL

| JOB NAME: | CATALOG NUMBERS: | |
|-------------|------------------|--|
| | | |
| JOB NUMBER: | | |

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

