



Color: Gray

UPC Code: 07847789207

Country Of Origin: Mexico



MT563-2SG

Brand Features

The Lev-Lok® Modular Wiring Device System is engineered for fast and easy installation. These devices employ a simple twist and lock wiring module that ensures a safe, reliable connection while at the same time providing for extremely fast and easy installation. Lev-Lok brand wiring devices address the reliability and performance concerns of specification engineers without sacrificing the contractor's need for fast, easy installation.

Item Description

Lev-Lok Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Two Outlets Marked "Controlled", Tamper-Resistant, Smooth Face, 20 Amp, 125 Volt, Modular, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding -

Gray

Mating Lev-Lok Wiring Module Required for Use

Technical Information

AC Horsepower Ratings Horsepower Rating: 1 HP

Electrical Specifications

Amperage: 20 A

Current Interrupting: Certified for current interrupting at full rated current Dielectric Voltage: Withstands 2000V per UL498 Grounding: Self-Grounding Pole: 2 Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current Voltage: 125 VAC Wire: 3

Environmental Specifications Flammability: Rated V-2 per UL94 Operating Temperature: -40°C to 60°C

Material Specifications

Base Material: Nylon Bushing: Solid Brass Cover Material: Nylon Ground Clips: Brass Line Contacts: 0.040" Thick Solid Brass Locking Pins: Solid Brass Mounting Screws: Triple Combination Head, Steel Mounting Strap: Galvanized Steel Shutter Mechanism: Acetal Mechanical Specifications

Product ID: Ratings are permanently marked on device Termination: Modular

Product Features

Brand: Lev-Lok

Color: Gray

Controlled Outlets: 2

Device Type: Duplex Receptacle Outlet **Feature:** Two Outlets Marked Controlled

Feature 2: Tamper-Resistant


Feature 4: Smooth Face

Grade: Heavy-Duty Industrial Specification Grade

NEMA: 5-20R

Standards and Certifications

ANSI: C-73 CSA C22.2 No. 42: File 152105 NEMA: WD-1 & WD-6 NOM: 057 UL498: File E13399 UL Fed Spec WC-596: File E13399 Warranty: 10 Year Limited



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

