




**Isostatic Industries, Inc.**  
 4153 North Kostner Avenue  
 Chicago, IL 60641  
**Toll Free:** 800.621.5500  
**Phone:** 773.286.3444  
**Fax:** 773.282.3323  
**Email:** [info@isostatic.com](mailto:info@isostatic.com)

## Item # 102910, Oilube® Powdered Metal Bronze SAE841 Rectangular Plates - INCH

### Isostatic Oilube® Rectangular Plates

- Standard stock products
- SAE 841-copper (87-90%), tin (8-9%), carbon, other elements
- Powdered metal bronze providing interconnected reservoirs for oil
- Vacuum impregnated with oil during the manufacturing process (approx. 19% by vol.)
- Self-lubricating – when in motion oil rises to the surface for lubrication and restores itself when at rest
- Ideal for heavy loads at moderate speeds or light loads at high speeds – max Pv 50,000, P-Load 2,000, V-SFM-1,200
- 



[+ more](#)

[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

### Description

#### Detailed Description

3/16 IN Thk. x 5 IN Wide x 6 IN Length, SAE 841 Powdered Metal Bronze, Flat Plate Stock

### Specifications

<b>Catalog Number</b>	PP-6000-1
<b>Interchange #</b>	PP 6000 01 PP6000-1
<b>Unit of Measure</b>	Each
<b>Material</b>	Powdered Metal / Oil Impregnated Bronze
<b>Material Standard</b>	SAE 841

**Avg Unit Weight** 1.4314 lb

**UPC Code** 00846802012113

Dimensions

**Nominal Length** 6 in

**Nominal Width** 5 in

**Nominal Plate Thickness** 1/5 in

Tolerances

**Overall Length Tolerance** Oversize - to finish to

**Width Tolerance** Oversize - to finish to

**Plate Thickness Tolerance**  $\pm$ .010 in

Performance Data

**Load - P Max Value** 2,000 lb/in<sup>2</sup>

**Speed - V Max Value** 1,200 ft<sup>2</sup>/min

**Load at Speed - PV Max Value (P.S.I. / S.F.M.)** 50,000