




Color: Red

UPC Code: 07847781888



8200-HR

Item Description

Duplex Receptacle Outlet, Heavy-Duty Hospital Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Red

Technical Information

AC Horsepower Ratings Horsepower Rating: 1/2 HP

Electrical Specifications

Amperage: 15 A Current Limiting: Full Rated Current Dielectric Voltage: Withstands 2000V per UL498 Grounding: Self-Grounding Pole: 2 Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current Voltage: 125 VAC

Wire: 3

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications Body Material: Nylon Clamp Nuts: Zinc-Plated Steel Color: Red Face Material: Nylon Ground Clips: Brass Grounding Screw: Brass Line Contacts: Phosphor Bronze Strap Material: Galvanized Steel with Riveted Ground Contacts Terminal Screws: Brass

Patents*

| CA2483480 | US6743029 |
|-----------|-----------|
| MX257790 | US8684771 |
| MX321216 | |

Mechanical Specifications **Product ID:** Markings are permanently marked on device **Terminal Accom.:** 14-10 AWG


Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Termination: Back or Side Wire Torque Range: 14-16 inch pounds


Product Features Color: Red Device Type: Duplex Receptacle Outlet Feature 4: Smooth Face Grade: Heavy-Duty Hospital Grade NEMA: 5-15R

Standards and Certifications ANSI: C-73 CSA C22.2 No. 42: File 152105 NEMA: WD-6 NOM: 057 RoHS: Non-Compliant UL498HG: File E13399 UL Fed Spec WC-596: File E13399 Warranty: 10-Year Limited

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.



Wiring Diagram



5-15R

SPECIFICATION SUBMITTAL

| JOB NAME: | CATALOG NUMBERS: | |
|-------------|------------------|--|
| | | |
| JOB NUMBER: | | |

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Teléfono: +1-800-323-8920 - EAX: +1-800-832-0538 - Tech Line (8:

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

