

Isostatic Industries, Inc. 4153 North Kostner Avenue Chicago, IL 60641 Toll Free: 800.621.5500 Phone: 773.286.3444 Fax: 773.282.3323 Email: info@isostatic.com

Item # 505012, TP® Lead Free Steel-Backed PTFE Lined Sleeve Bearings - INCH

Isostatic TP® Sleeve Bearings

- Standard stock products
- Self-lubricating dry sliding bearing
- A steel-backed composite material comprised of:
 - Low carbon steel backing for extremely high load capacity .50 2.7 mm thick
 - Sintered bronze offers optimal heat dispersion .20 .35 mm thickness and
 - PTFE lead free sliding surface creates a low friction coefficient and allows for a wide temperature range thickness .2 mm
- Can be used where many liquid lubricants fail; also performs well with



Description | Specifications | Dimensions | Tolerances | Performance Data

Description		-
Detailed Description	.375 IN I.D. x .4688 IN O.D. x 0.1875 IN Length, TP, Lead Free Steel Back, PTFE Lined Composite, Sleeve Bearing	
Specifications		-
Catalog Number	06TP03	
Interchange #	06DP403 EGBZ0603-E40	
Unit of Measure	Each	
Material	Lead Free Steel-Backed PTFE	
Material Standard	Lead Free Steel-Backed PTFE	

+ more

1/8/2018	Page	2 of	2
----------	------	------	---

Avg Unit Weight 0.0031 lb	Dim	nensions	
Avg Unit Weight 0.0031 lb		UPC Code	00846802077143
		Avg Unit Weight	0.0031 lb

Nominal Inner Diameter	3/8 in
Nominal Outer Diameter	15/32 in
Nominal Length	3/16 in
Recommended Shaft Size	.3731 to .3740 in
Recommended Housing Bore	.4684 to .4691 in

Tolerances

Γ

Overall	Longth	Toloropoo
Overall	Length	Tolerance

Performance Data

Load - P Max Value	36,250 lb/in ²
Speed - V Max Value	1,900 ft²/min
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	102,000

±.01 in