

SUBMITTAL SHEET

TAP'T™ COUPLING

GASKET X GASKET X FEMALE ACME



JOB NAME	
JOB LOCATION	
ENGINEER	
CONTRACTOR	
TAG	
PO NUMBER	
REPRESENTATIVE	
WHOLESALE DISTRIBUTOR	

- No solvent cement needed
- Gasketed connection on the run
- ACME thread on the branch
- 315 psi working pressure (1008 psi burst test pressure per ASTM F-1970)
- Tap't™ Couplings are not directional fittings so thrust blocking is not required unless they are installed at the end of a lateral line

SPECIFICATIONS:

Maximum Working Pressure: 315 psi @ 73 deg F

ASTM D1784 - Rigid Poly (Vinyl Chloride) (PVC) Compounds and Chlorinated Poly Vinyl Chloride (CPVC) Compounds

ASTM D1970 - for Special Engineered Fittings, Appurtenances or Valves for use in Poly (Vinyl Chloride) (PVC)

SUGGESTED SPECIFICATIONS:

Tap't™ Coupling gasketed service fittings as manufactured by LASCO Fittings, Inc. shall be utilized where indicated on plan, molded of rigid polyvinyl chloride (PVC), Type 1 cell classification 1254 per ASTM standard D- 1784 and meet ASTM standard F-1970 for Special Engineered Fittings, Appurtenances or Valves for use in Poly (Vinyl Chloride) (PVC).

MATERIALS:

PVC Type 1 Cell Classification 12454-B

HOW TO ORDER:

PART #	DESC	SIZE	CTN QTY
344-251	Coupling	2 x 2 x 1½	15
344-291	Coupling	2½ x 2½ x 1½	15
344-337	Coupling	3 x 3 x 1½	10
344-419	Coupling	4 x 4 x 1½	5

WARRANTY:

Five Year Limited Performance Warranty

LASCO Fittings, Inc. products are warranted to be free from manufacturing defects in materials and workmanship. They are warranted against rot, rust, and electrolytic corrosion for a period of five years from date of installation. If LASCO products prove defective due to manufacturing defects in material or workmanship during that period, the manufacturer will provide new replacement units of the same type and size. No remedy will be granted under this warranty if LASCO products are not used strictly in accordance with LASCO's directions with respect to use and storage or if the products have been modified in any way.

THE MANUFACTURER'S LIABILITY UNDER EXPRESSED OR IMPLIED WARRANTY OR FOR ANY REASON IS LIMITED TO FURNISHING REPLACEMENT UNITS OR GRANTING A CREDIT FOR DEFECTIVE UNITS. NO LABOR EXPENSE OR CONSEQUENTIAL DAMAGES WILL BE PAID BY LASCO. THIS WARRANTY IS IN LIEU OF ALL OTHER GUARANTEES AND WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PURPOSE, EXCEPT FOR ANY WARRANTIES IMPLIED BY LAW FOR NONCOMMERCIAL CONSUMERS. ANY SUCH WARRANTIES ARE LIMITED TO THE DURATION OF THIS WRITTEN WARRANTY.

DO NOT USE LASCO FITTINGS FOR COMPRESSED AIR OR GASES.
DO NOT TEST PVC PIPING SYSTEMS WITH COMPRESSED AIR OR GASES.
DO NOT USE FITTINGS WITH LIQUIDS NOT RECOMMENDED BY LASCO.
MODIFICATIONS OF FITTINGS VOIDS THE WARRANTY.

414 Morgan Street • Brownsville, TN 38012
(731) 772-3180 | www.lascofittings.com

This specification is provided for reference only. LASCO Fittings, Inc reserves the right to change nay portion of this specification without notice and without incurring obligation to make such changes to LASCO products previously or subsequently sold. Please visit our website www.lascofittings.com for the most current information.