



# Technical Data Sheet

## RINZ OFF®

### Water Removable / Temporary Ink

#### FEATURES

- Water removable / temporary ink marker that makes temporary marks on non-treated, non-painted and non-porous metal and glass surfaces.
- Marks can easily be removed with a water
- The removed marks won't "ghost" or bleed through when painted over.
- Markers can be used to temporarily identify inventory, assemblies, tools, work in progress or finished products.
- Ideal for quality control, part assembly, identification, site inspection and more.
- Easy identification of pressure points or defects in metal.
- Valve action mechanism prevents paint in barrel from drying when the cap is left off.
- 44 style marker features a threaded barrel that can be screwed into a jig or fixture for a continuous marking process.
- Heavy duty aluminum body with large paint capacity.
- Bullet tips are replaceable to assure complete use of ink in each marker.
- Does not contain any reportable amounts of Xylene.

#### MATERIALS COMPATIBILITY

- Safe on non-treated, non-painted and non-porous metal and glass surfaces.
- Removable with water.
- Surface tests should be run to determine compatibility prior to use.

#### AVAILABLE IN:

| <u>Colors</u> | <u>Medium</u> | <u>44</u> |
|---------------|---------------|-----------|
| Black         | 91109         | N/A       |
| Blue          | 91105         | 44105     |
| Green         | 91108         | 44108     |
| Red           | 91106         | 44106     |
| White         | N/A           | 44709     |
| Yellow        | 91757         | 44757     |

#### HEALTH AND SAFETY

- Flammable liquid and vapor. Keep away from heat, sparks and flame. Use only with adequate ventilation. Avoid contact with skin and eyes.
- Refer to SDS (Safety Data Sheet) for complete information on health and safety. Visit our website to obtain SDS.

#### DIRECTIONS FOR USE

- Depress tip to start flow
- Replace cap when not in use

#### PHYSICAL PROPERTIES

|                   |                     |
|-------------------|---------------------|
| Appearance:       | Varies              |
| Odor:             | Alcohol             |
| Specific gravity: | See MSDS            |
| VOC level:        | 77% - 92% by weight |
| Flash point:      | See MSDS            |
| Dry Time*:        | 45 - 60 seconds     |

\* Note: Drying time may vary depending on film thickness.