



Product Number: 72966

Order Abbreviation: SLMWPK1A/030347750/CO/BZ

General Description: Slim Wallpack1A, 30 Watts, 347V, 70+ CRI, 5000K, bronze finish

Product Information

Power Factor	?.90
Primary Lamp Type	COB
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Primary Lamp Type 1	COB
Total Harmonic Distortion (THD)	?20 %
Efficacy (LPW)	30
Abbrev. With Packaging Info.	SLMWPK1A030347750COBZ 1/CS 1/SKU
Color Temperature/CCT (K)	5000
Ordering Abbreviation	SLMWPK1A/030347750/CO/BZ
Average Rated Life 1 (hr)	125000
Lumens	3400
Nominal Voltage (V)	347.00
Nominal Wattage (W)	30.00
UPC Code	UPC046135729669
Color Rendering Index (CRI)	>70
Service Life Rating	?125000
Lumens (lm)	3400
Wattage (W)	30.00
Color Range	5000 K
Connectors	Flying leads
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	Bronze
Luminaire Type	Wall pack
Maximum Operating Temperature-Celsius	40
Maximum Operating Temperature-Fahrenheit	104
Power Input	30
Mounting	Surface
Dimensions	7.5x2.8x8
Certification Listing	cULus, FCC, RoHS, DLC