

MINI METER KITS

Note: Kits include meter, specified enclosure and required current transformers

Mini Meter Kits - Indoor Flush Mount Enclosure

| VOLTAGE | AMPS | CTS INCLUDED | CAT. NO. |
|--|------|--------------|-----------|
| 120/208V 3W or 120/240V 1PH 3W (Split Phase) | 100A | 2 SOLID CTs | MK240-1SW |
| | 200A | 2 SOLID CTs | MK240-2SW |

Mini Meter Kits - Outdoor Enclosure

| VOLTAGE | AMPS | CTS INCLUDED | CAT. NO. |
|--|------|--------------|-----------|
| 120/208V 3W or 120/240V 1PH 3W (Split Phase) | 100A | 2 SOLID CTs | MO240-1SW |
| | 200A | 2 SOLID CTs | MO240-2SW |
| 120/208V 2PH 3W or 120/240V 1PH 3W (Split Phase) | 100A | 2 Split CTs | MO240-01W |
| | 200A | 2 Split CTs | MO240-02W |

0.5% Mini Meter Kits - Indoor Flush Mount Enclosure*

| VOLTAGE | AMPS | CTS INCLUDED | CAT. NO. |
|--|-------|--------------|-----------|
| 120/208/240V 2PH 3W | 200 A | 2 SOLID CTs | 6P201-Co2 |
| 120/208/240V 2PH 3W (includes Time of Use (TOU)) | 200 A | 2 SOLID CTs | 6W201-Co2 |
| 120/208/240V 2PH 3W (includes Time of Use (TOU) & Temperature) | 200 A | 2 SOLID CTs | 6W201-Do2 |
| 120/208/240V 2PH 3W (includes Time of Use (TOU) & Delta Temperature) | 200 A | 2 SOLID CTs | 6W201-Eo2 |
| 120/208/240V 2PH 3W (OEM Module Kit) | 200 A | 2 SOLID CTs | 7H201-So2 |

0.5% Mini Meter Kits - Indoor Surface Mount Enclosure*

| VOLTAGE | AMPS | CTS INCLUDED | CAT. NO. |
|--|-------|--------------|-----------|
| 120/208/240V 2PH 3W | 200 A | 2 SOLID CTs | 6PSMT-Co2 |
| 120/240V 1PH 3W (includes Time of Use (TOU) enabled kWh Transceiver) | 200 A | 2 SOLID CTs | MMSMT-Co2 |
| 120/240V 1PH 3W (includes Time of Use (TOU) and Temperature enabled kWh Transceiver) | 200 A | 2 SOLID CTs | MMSMT-Do2 |
| 120/240V 1PH 3W (includes Time of Use (TOU) and Delta Temperature enabled kWh Transceiver) | 200 A | 2 SOLID CTs | MMSMT-Eo2 |

Wireless Repeater

| CAT. NO. | DESCRIPTION |
|-----------|---|
| T101R-05V | Repeater, 5V, includes 5VDC 1A plug-in power supply and internal backup battery |

Wireless Data Concentrating Access Points (DCAPs)**

| CAT. NO. | DESCRIPTION |
|-----------|--|
| T201E-151 | Data Concentrating Access Point (DCAP), Low Capacity (150 meter points max), built-in radio receiver |
| T201E-102 | DCAP, High Capacity (1000 meter points max), built-in radio receiver |
| T201G-UNL | DCAP-Gateway, unlimited meter points, built-in radio receiver |
| T221C-202 | Central Database Gateway, supports up to 2000 meter points |

*For a complete wireless Automatic Meter Reading (AMR) system, data transceivers and other wireless network components (DCAPs and Repeaters) are required as dictated by building construction.

TOU = Time of Use, providing 15-minute time-stamped kWh interval data

**All DCAPs and Gateways shipped with 6VDC, minimum 1.5 Amp power supply, Ethernet cable and USB cable