

## 63MM & 75MM METRIC X ACME SERVICE TEES & ELBOWS



- Use the proven ACME O-ring Service Seal fittings to provide leak-free connection to the LASCO Swing Joint.
- The ACME Service Seal fittings do not require Teflon<sup>®</sup> or thread sealant.
- ACME Service Seal fittings improve installation and lower maintenance costs.
- Designed expressly for LASCO Swing Joints with either the “M” or “P” inlet connection.
- Service Tee and Service Elbow for mainline, laterals & end-of-line connections.
- Solvent cement for welded joint line connections.
- 1 1/2” Female ACME threads on the swing joint port to eliminate splitting & cracking.
- Rated at 315 p.s.i. per ASTM F1970.



| Service Tee |                   |            |      |
|-------------|-------------------|------------|------|
| Part No     | Nominal Size (in) | Carton Qty | Code |
| 7302-JJ-015 | 63mm x 1½         | 10         | 08   |
| 7302-KK-015 | 75mm x 1½         | 10         | 08   |

| Service Elbow |                   |            |      |
|---------------|-------------------|------------|------|
| Part No       | Nominal Size (in) | Carton Qty | Code |
| 7307-J-015    | 63mm x 1½         | 10         | 08   |
| 7307-K-015    | 75mm x 1½         | 10         | 08   |

### STANDARDS AND SPECIFICATIONS

- ASTM F-1970 – Standard Specification for Special Engineered Fittings, Appurtenances or Valves for use in Poly (Vinyl Chloride) (PVC) or Chlorinated Poly (Vinyl Chloride) (CPVC) Systems.
- ASTM F-2768 – ACME Thread Joint with Elastomeric Seal in Plastic Piping Components
- MATERIAL – Sch 80 Type 1 PVC