



Product Number: 67699

Order Abbreviation: LU70/PLUS/XL/ECO

General Description: 70W High Pressure Sodium lamp, 80,000 hour rated life, noncycling, instant restrike, TCLP, environmentally friendly, ET23.5, E39 base, universal operation, clear, CCT1900

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	LU70PLUSXLECO 20/CS 1/SKU
ANSI Code	S62
ANSI Code 2	S62
Approx. Lumens (initial - horizontal)	6150
Approx. Lumens (initial - vertical)	6150
Approx. Lumens (mean - horizontal)	4950
Approx. Lumens (mean - vertical)	4950
Arc Length (in)	1.09
Arc Length (mm)	27.6
Average Rated Life - Horizontal (hr)	80000
Average Rated Life - (hr)	80000
Average Rated Life - Vertical (hr)	80000
Avg Rated Life (hrs)	80000
Base	E39 Mogul
Bulb	ET23.5
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	1900
Diameter (in)	2.937
Diameter (mm)	74.59
Family Brand Name	Lumalux PLUS® XL Ecologic®
Fixture Requirement	O
Hot Restrike Time (min)	INSTANT
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	7.75
Maximum Overall Length - MOL (mm)	197
Nominal Voltage (V)	52.00
Nominal Wattage (W)	70.00
Operating Position	Universal

Warm-up Time (min)

3-4 MINUTES