



Color: White

## UPC Code: 07847781942



# 16262-W

## **Brand Features**

Leviton's line of Extra Heavy-Duty Industrial Grade receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

### **Item Description**

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

### **Technical Information**

AC Horsepower Ratings At Rated Voltage: 1/2 HP

# **Electrical Specifications**

Grounding: Self-Grounding Amperage: 15 A Voltage: 125 VAC Pole: 2 Wire: 3 Dielectric Voltage: Withstands 2000V per UL498 Current Limiting: Full Rated Current

Temperature Rise: Max 30C at 250 cycles OL at 200 pct rated current

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications

Face Material: Thermoplastic Nylon Body Material: Thermoplastic Nylon Line Contacts: Brass Triple-Wipe .031 Thick

Terminal Screws: Brass 10-32 Grounding Screw: Brass 8-32 Strap Material: Zinc-Plated Steel Clamp Nuts: Zinc-Plated Steel Ground Clips: Brass-Plated Color: White Mechanical Specifications **Terminal ID:** Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 14-10 AWG Product ID: Ratings are permanently marked on device Termination: Back or Side Wire

Product Features


NEMA: 5-15R

Color: White


Device Type: Duplex Receptacle Outlet Feature 4: Smooth Face Grade: Heavy-Duty Industrial Specification Grade Brand: Decora Plus

Standards and Certifications NEMA: WD-6 ANSI: C-73 UL498: File E13399 CSA C22.2 No. 42: File 152105 NOM: 057 Warranty: 10 Year Limited

# **Dimensional Diagram**



Wiring Diagram



5-15R

# SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

# Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

# Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

