

UPC Code: 07847723916

1223-7LI

Brand Features

Leviton's Industrial Grade AC toggle switches for extra heavy-duty applications represent top-of-the-line quality and peak performance. Leviton uses the finest materials available and the highest production standards to produce industrial switches of unmatched versatility and reliability.

Item Description

20 Amp, 277 Volt, Toggle Lighted Handle - Illuminated OFF 3-Way AC Quiet Switch, Industrial Grade, Self Grounding, Back &Side Wired, - Ivory

Technical Information

AC Horsepower Ratings HP Rating: 1HP-120V Max. Amperage: 16 Amp

Electrical Specifications Amperage: 20 A Voltage: 277 VAC Grounding: Self-Grounding Dielectric Voltage: Withstands 1500V for 1 minute Overload UL20 Test: 100 cycles of OL at 4.8 times rated current Temperature Rise: Maximum 30 degrees C rise

Endurance: 50,000 cycles minimum

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 65°C

Material Specifications Strap Material: .048" Thick Galvanized Steel Base Material: Thermoplastic Toggle: Polycarbonate Cover Material: Thermoplastic Contact Material: Silver Alloy

Terminal Screws: Brass 8-32 Grounding Screw: Brass 8-32 Ground Clips: Brass Color: Ivory Mechanical Specifications Terminal ID: Brass-Hot Black-Hot White-Neutral Green-Gnd

Terminal Accom.: 14-#10 AWG back wired; #14-#12 AWG side wired

Product ID: Ratings are permanently marked on device

Torque Range: 12-14 inch pounds **Termination:** Back or Side Wire


Product Features

Color: Ivory Function: 3-Way Grade: Extra Heavy-Duty Industrial Specification Grade Feature 2: Illuminated - Load OFF Device Type: Toggle Switch


Standards and Certifications NEMA: WD-1 & WD-6 ANSI: C-73 UL Fed Spec WS896E: File #E7458 UL Standard: UL 20 CSA C22.2 No. 111: File #152105 NOM: 057 RoHS: Compliant Warranty: 10 Year Limited



Dimensional Diagram



Wiring Diagram 3-Way Lighted



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

