



Color: Ivory

UPC Code: 07847736423

Country Of Origin: Mexico



# M1636-I

## **Brand Features**

The Lev-Lok® Modular Wiring Device System is engineered for fast and easy installation. These devices employ a simple twist and lock wiring module that ensures a safe, reliable connection while at the same time providing for extremely fast and easy installation. Lev-Lok brand wiring devices address the reliability and performance concerns of specification engineers without sacrificing the contractor's need for fast, easy installation. Available in extra heavy duty hospital and industrial grades, and heavy duty commercial grade platforms.

### Item Description

Lev-Lok Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 20 Amp, 125 Volt, Modular, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Ivory<br><sbr><strong>Mating Lev-Lok Wiring Module Required for Use</strong>

#### **Technical Information**

AC Horsepower Ratings Horsepower Rating: 1 HP

Electrical Specifications

Amperage: 20 A Voltage: 125 VAC

**Pole:** 2

Wire: 3

Grounding: Self-Grounding Dielectric Voltage: Withstands 2000V

per UL498

Maximum Working Voltage: 125V as rated

**Current Interrupting:** Certified for current interrupting at full rated current **Temperature Rise:** Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications Flammability: Rated V-2 per UL94 Operating Temperature: -40°C to 60°C

Material Specifications

Cover Material: Nylon Base Material: Nylon Mounting Strap: Galvanized Steel with Riveted Ground Contacts

Ground Clips: Brass

Line Contacts: 0.040" Thick Solid Brass

Locking Pins: Solid Brass Mounting Screws: Triple Combination Head, Steel Mechanical Specifications

Product ID: Ratings are permanently marked on device Termination: Modular


Product Features

Color: Ivory


NEMA: 5-20R Device Type: Duplex Receptacle Outlet Feature 4: Smooth Face Grade: Heavy-Duty Industrial Specification Grade Brand: Lev-Lok Decora Plus

Standards and Certifications

NEMA: WD-1 & WD-6 cULus: Listed NOM Certified: 057 ANSI: C-73 Warranty: 10 Year Limited



# Wiring Diagram



5-20R

# SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

## Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

