



Color: N/A White, Ivory, Light Almond

UPC Code: 07847772856 Country Of Origin: China

DDMX1-BLZ

Brand Features

The next generation of lighting control technology is here with the new Decora® Digital Controls with Bluetooth® technology - a powerful device combining the best of Leviton dimmer and timer functions with today's technology. Just use your smartphone or tablet and the Decora Digital Dimmer &Timer app to control, adjust and time lighting for daily activities or to ensure a "lived-in" look while away. Decora Digital Controls with Bluetooth technology provide local control within a 30 foot* range without the need of a hub, gateway or internet connection, bridging the gap between traditional dimmers and whole-house automation systems.

*30-foot Bluetooth range: Range may vary depending on specific conditions on installation, configuration of walls, obstacles and other factors.

Item Description

Decora Digital Universal Dimmable LED, CFL and Incandescent Digital Dimmer and 24 hour Timer, 1000W-120VAC Incandescent, 450W-120VAC Dimmable LED and CFL, 1000 VA Mark 10, 1000 VA MLV, 60Hz, Single Pole and 3-Way/multi-location control, LED locator and brightness display. White face assembled on device, Ivory and Light Almond faces included. Neutral wire required for installation. - White, Ivory, Light Almond

Technical Information

Product Features

Action: Soft-On, Fade-Off. Rocker Switch for ON/OFF, Dimmer bar for lighting level

control

California Title 24: Yes

Color: White, Ivory, Light Almond

LED Color: Green

Light: LED Locator and Brightness Display

Load Rating: 450W LED and CFL, 1000W Incandescent, 1000 VA Mark 10, 1000

VA MLV

Load Type: Incandescent, Dimmable LED, Dimmable CFL, Mark 10, MLV

NEMA SSL 7A: Yes

Ordering Notes: Included White, Ivory and Light Almond Color Kit

Preset: Slide bar preserves desired lighting level

Standards and Certifications: CSA, NOM, Bluetooth SIG, FCC

Style Name: Decora

Switch Type: Single-Pole, 3-Way or More Applications

Timer Type: 24 Hour

Type: Digital Voltage: 120 VAC

Wallplate: Order Separately Warranty: 5-Year Limited

Wireless Connectivity: Bluetooth

Features and Benefits

- Digital circuitry provides programmable soft fade on and fade off
- Ability to set maximum light level for energy savings
- App is Compatible with Apple and Android smartphones or tablets
- Uses simple, intuitive on-screen menu options
- Individually control and program dimmers and switches within the home
- Each device can be uniquely named for easy identification
- Flexibility to program timed events weekdays,weekends or any combination of days at set or random times
- Astronomical clock automatically adjusts to local sunrise/sunset times
- Automatic daylight saving time adjustment
- Countdown sleep timer can be set for up to 12 hours
- LED locator light can be turned off via app
- Dimmer brightness display can be turned off via app
- Single pole or 3-way/multi-location control with Decora Digital remote (sold separately)
- No fins for multi-gang installation
- Built-in radio/TV interference filter
- Neutral wire required
- Can be used to comply with 2016 California Title 24, Part 6 Indoor Lighting Switching Devices and Controls

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

