

## GFA15-100



**UPC Code:** 07847742069

**Country of Origin:** China

## Portable GFCI Devices

### Brand Features

Portable GFCI Devices from Leviton are now sleeker and more rugged than ever! And, while these devices are fully OSHA compliant for use on job sites, they are also perfect for use in a variety of temporary power applications, such as recreation vehicles, marine vehicles, portable pools, portable generators, submersible pumps, vending machines and more.

### Item Description

15 Amp, 120 Volt, 100 ft. Cord Set, Molded-On NEMA Plug (5-15P) and Connector (5-15R), Straight Blade, Automatic Reset GFCI Device, 14-3 SJTW Cord, UL/CSA Listed

### Technical Information

#### AC Horsepower Ratings

**At Rated Voltage:** 3/4 Horsepower

#### Electrical Specifications

**Amperage:** 15 Amp

**Voltage:** 120 Volt

**NEMA:** 5-15P

**Pole:** 2

**Wire:** 3

**Current Interrupting:** 2 kA

**Trip Level:** 5mA plus or minus 1mA

#### Environmental Specifications

**Flammability:** Rated V-2 per UL94

**Operating Temperature:** -35C - 66C

#### Material Specifications

**Cord Type:** 14/3 SJTW

**Body Material:** Polycarbonate

**Blades/Contacts:** Brass

#### Mechanical Specifications

**Product ID:** Ratings marked on device label

#### Standards and Certifications

**NEMA:** WD-6

**ANSI:** C-73

**NOM:** 057

**Warranty:** 2-Year Limited

**Applicable Standards:** UL 943, UL 498, CSA C22.2 No. 42 & 144

### Features and Benefits

- Rainproof, Outdoor rated GFCI Module.
- Fully complies with NEC and OSHA regulations for construction sites.
- Automatically resets to ON when plugged in or after power interruption.
- Power Indicator lamp goes OFF if GFCI trips, power is interrupted or line cord is unplugged.
- Open-Neutral Protection immediately trips the GFCI if the neutral conductor on the line side is opened, eliminating the possibility of the GFCI Cord Set having a live hot leg.
- Inline GFCI unit features a rainproof, ultrasonically welded enclosure to ensure long service life.

## SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 ·

FAX: 1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2012-2018 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to: [www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

