





UPC Code: 07847706764

Country Of Origin: Mexico



69W82

30 Amp, 277/480 Volt 3-Phase Y, NEMA L22-30R, 4P, 5W, Flush Mtg Locking Receptacle, Industrial Grade, Grounding, Wetguard w/Cover - YELLOW

Leviton's Wetguard line of industrial watertight wiring devices are the most versatile, well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive brands.

Technical Information

AC Horsepower Ratings At Rated Voltage: 10 HP

Electrical Specifications

Current Limiting: Full Rated Current Dielectric Voltage: Withstands 2000V per UL498

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current Phase: 3-Phase WYE

Environmental Specifications

Environment: Wet Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications


Base Material: Nylon Face Material: Nylon Grounding Screw: Brass 8-32 Line Contacts: Brass .040 Thick Terminal Screws: Brass 10-32 Yoke: Nickel-Plated Brass .050 Thick

Mechanical Specifications


Product ID: Ratings and NEMA I.D. permanently marked on device Terminal Accom.: 14-8 AWG Terminal ID: Brass-Hot, Green-Ground, White-Neutral **Product Features** Amperage: 30 A Base Material: Nylon Brand: Wetguard Color: Yellow Face Material: Nylon Grounding: Grounding NEMA: L22-30R Pole: 4 Standards and Certifications: UL/CSA Strap Material: Nickel-Plated Brass Termination: Back Voltage: 277/480 VAC Warranty: Lifetime Warranty Wire: 5 Device Type: Locking Outlet Standards and Certifications ANSI: C-73

CSA C22.2 No. 42: File LR-406 NEMA: WD-6 NOM: 057 UL498: File E13399 UL Fed Spec WC-596: File E13399

Dimensional Diagram



Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

